

E2A-M12LS04-WP-B2 5M

Product description	M12LNG,SHLD,NPB,4MM,PNP,NC,5M
RoHs Status	Memimpin percuma / RoHS Compliant
Stock Condition	1070 pcs stock
Ship From	Hong Kong
Shipment Way	DHL/Fedex/TNT/UPS/EMS



Spesifikasi E2A-M12LS04-WP-B2 5M

NOMBOR BAHAGIAN	E2A-M12LS04-WP-B2 5M
PENGELUAR	Omron Automation & Safety
PENERANGAN	M12LNG,SHLD,NPB,4MM,PNP,NC,5M
STATUS STATUS PERCUMA / ROSH STATUS	Memimpin percuma / RoHS Compliant
KUANTITI TERSEDIA	1070 pcs
LEMBARAN DATA	
VOLTAN - BEKALAN	10 V ~ 32 V
STYLE PENAMATAN	Cable Leads
PERISAI	Shielded
SIRI	E2A
JENIS SENSOR	Inductive
SENSING JARAK	0.157" (4mm)
RESPON FREKUENSI	1kHz
PAKEJ / KES	Cylinder, Threaded - M12
JENIS OUTPUT	PNP-NC, 3-Wire
NAMA LAIN	E2A-M12LS04-WP-B2 5M-ND E2A-M12LS04-WP-B25M E2AM12LS04WPB25M
SUHU OPERASI	-40°C ~ 70°C
TAHAP SENSITIVITI LEMBAPAN (MSL)	1 (Unlimited)
BAHAN - BADAN	Nickel-Plated Brass
STATUS STATUS PERCUMA / ROSH STATUS	Lead free / RoHS Compliant
PERLINDUNGAN INGRESS	IP67, IP69K
PETUNJUK	LED
PENERANGAN TERPERINCI	Inductive Proximity Sensor 0.157" (4mm) IP67, IP69K Cylinder, Threaded - M12