



Omron Automation & Safety



E2A-M18KN16-WP-C1 5M

|                   |                                   |
|-------------------|-----------------------------------|
| Penerangan Produk | PROXIMITY SENSOR M18 16MM NPN     |
| Status RoHS       | Memimpin percuma / RoHS Compliant |
| Kadaan Stok       | 855 pcs stock                     |
| Kapal Dari        | Hong Kong                         |
| Cara Penghantaran | DHL/Fedex/TNT/UPS/EMS             |

Spesifikasi E2A-M18KN16-WP-C1 5M

|                                     |                                                                                                                               |
|-------------------------------------|-------------------------------------------------------------------------------------------------------------------------------|
| NOMBOR BAHAGIAN                     | E2A-M18KN16-WP-C1 5M                                                                                                          |
| PENGELUAR                           | Omron Automation & Safety                                                                                                     |
| PENERANGAN                          | PROXIMITY SENSOR M18 16MM NPN                                                                                                 |
| STATUS STATUS PERCUMA / ROSH STATUS | Memimpin percuma / RoHS Compliant                                                                                             |
| KUANTITI TERSEDIA                   | 855 pcs                                                                                                                       |
| LEMBARAN DATA                       |                                                                                                                               |
| VOLTAN - BEKALAN                    | 10 V ~ 32 V                                                                                                                   |
| STYLE PENAMATAN                     | Cable Leads                                                                                                                   |
| PERISAI                             | Unshielded                                                                                                                    |
| SIRI                                | E2A                                                                                                                           |
| JENIS SENSOR                        | Inductive                                                                                                                     |
| SENSING JARAK                       | 0.63" (16mm)                                                                                                                  |
| RESPON FREKUENSI                    | 400Hz                                                                                                                         |
| PAKEJ / KES                         | Cylinder, Threaded - M18                                                                                                      |
| JENIS OUTPUT                        | NPN-NO, 3-Wire                                                                                                                |
| NAMA LAIN                           | E2A-M18KN16-WP-C1 5M-ND<br>E2A-M18KN16-WP-C15M<br>E2A-M18KN16-WP-C15M-ND<br>E2A/M18KN16/WP/C1 5M<br>E2AM18KN16WPC15M<br>Z9128 |
| SUHU OPERASI                        | -40°C ~ 70°C                                                                                                                  |
| TAHAP SENSITIVITI LEMBAPAN (MSL)    | 1 (Unlimited)                                                                                                                 |
| BAHAN - BADAN                       | Nickel-Plated Brass                                                                                                           |
| STATUS STATUS PERCUMA / ROSH STATUS | Lead free / RoHS Compliant                                                                                                    |
| PERLINDUNGAN INGRESS                | IP67, IP69K                                                                                                                   |
| PETUNJUK                            | LED                                                                                                                           |
| PENERANGAN TERPERINCI               | Inductive Proximity Sensor 0.63" (16mm) IP67, IP69K Cylinder, Threaded - M18                                                  |