

E2A-M18KS08-M1-B3

Product description	PROXIMITY SENS M18 8MM PNP NO+NC
RoHs Status	Lead free / RoHS Compliant
Stock Condition	821 pcs stock
Ship From	Hong Kong
Shipment Way	DHL/Fedex/TNT/UPS/EMS



Specifications of E2A-M18KS08-M1-B3

PART NUMBER	E2A-M18KS08-M1-B3
MANUFACTURER	Omron Automation & Safety
DESCRIPTION	PROXIMITY SENS M18 8MM PNP NO+NC
LEAD FREE STATUS / ROHS STATUS	Lead free / RoHS Compliant
QUANTITY AVAILABLE	821 pcs
DATA SHEET	
VOLTAGE - SUPPLY	10 V ~ 32 V
TERMINATION STYLE	Connector
SHIELDING	Shielded
SERIES	E2A
SENSOR TYPE	Inductive
SENSING DISTANCE	0.315" (8mm)
RESPONSE FREQUENCY	500Hz
PACKAGE / CASE	Cylinder, Threaded - M18
OUTPUT TYPE	PNP-NC/NO, 3-Wire
OTHER NAMES	E2A-M18KS08-M1-B3-ND E2A/M18KS08/M1/B3 E2AM18KS08M1B3 Z9131
OPERATING TEMPERATURE	-40°C ~ 70°C
MOISTURE SENSITIVITY LEVEL (MSL)	1 (Unlimited)
MATERIAL - BODY	Nickel-Plated Brass
LEAD FREE STATUS / ROHS STATUS	Lead free / RoHS Compliant
INGRESS PROTECTION	IP67, IP69K
INDICATOR	LED
DETAILED DESCRIPTION	Inductive Proximity Sensor 0.315" (8mm) IP67, IP69K Cylinder, Threaded - M18