



E2A-M30KS15-M1-B3

Penerangan Produk	PROXIMITY SENSOR M30 15MM PNP
Status RoHS	Memimpin percuma / RoHS Compliant
Keadaan Stok	735 pcs stock
Kapal Dari	Hong Kong
Cara Penghantaran	DHL/Fedex/TNT/UPS/EMS

Spesifikasi E2A-M30KS15-M1-B3

NOMBOR BAHAGIAN	E2A-M30KS15-M1-B3
PENGELUAR	Omron Automation & Safety
PENERANGAN	PROXIMITY SENSOR M30 15MM PNP
STATUS STATUS PERCUMA / ROSH STATUS	Memimpin percuma / RoHS Compliant
KUANTITI TERSEDIA	735 pcs
LEMBARAN DATA	
VOLTAN - BEKALAN	10 V ~ 32 V
STYLE PENAMATAN	Connector
PERISAI	Shielded
SIRI	E2A
JENIS SENSOR	Inductive
SENSING JARAK	0.591" (15mm)
RESPON FREKUENSI	250Hz
PAKEJ / KES	Cylinder, Threaded - M30
JENIS OUTPUT	PNP-NC/NO, 3-Wire
NAMA LAIN	E2A/M30KS15/M1/B3 E2AM30KS15M1B3
SUHU OPERASI	-40°C ~ 70°C
TAHAP SENSITIVITI LEMBAPAN (MSL)	1 (Unlimited)
BAHAN - BADAN	Nickel-Plated Brass
STATUS STATUS PERCUMA / ROSH STATUS	Lead free / RoHS Compliant
PERLINDUNGAN INGRESS	IP67, IP69K
PETUNJUK	LED
PENERANGAN TERPERINCI	Inductive Proximity Sensor 0.591" (15mm) IP67, IP69K Cylinder, Threaded - M30