

E2A-M30KS15-WP-B3 2M



Product description

PROXIMITY SENSOR M30 15MM PNP

RoHs Status

Lead free / RoHS Compliant

Stock Condition

741 pcs stock

Ship From

Hong Kong

Shipment Way

DHL/Fedex/TNT/UPS/EMS

Specifications of E2A-M30KS15-WP-B3 2M

PART NUMBER	E2A-M30KS15-WP-B3 2M
MANUFACTURER	Omron Automation & Safety
DESCRIPTION	PROXIMITY SENSOR M30 15MM PNP
LEAD FREE STATUS / ROHS STATUS	Lead free / RoHS Compliant
QUANTITY AVAILABLE	741 pcs
DATA SHEET	
VOLTAGE - SUPPLY	10 V ~ 32 V
TERMINATION STYLE	Cable Leads
SHIELDING	Shielded
SERIES	E2A
SENSOR TYPE	Inductive
SENSING DISTANCE	0.591" (15mm)
RESPONSE FREQUENCY	250Hz
PACKAGE / CASE	Cylinder, Threaded - M30
OUTPUT TYPE	PNP-NC/NO, 3-Wire
OTHER NAMES	E2A-M30KS15-WP-B3 2M-ND E2A-M30KS15-WP-B32M E2A-M30KS15-WP-B32M-ND E2A/M30KS15/WP/B3 2M E2AM30KS15WPB32M Z9142
OPERATING TEMPERATURE	-40°C ~ 70°C
MOISTURE SENSITIVITY LEVEL (MSL)	1 (Unlimited)
MATERIAL - BODY	Nickel-Plated Brass
LEAD FREE STATUS / ROHS STATUS	Lead free / RoHS Compliant
INGRESS PROTECTION	IP67, IP69K
INDICATOR	LED
DETAILED DESCRIPTION	Inductive Proximity Sensor 0.591" (15mm) IP67, IP69K Cylinder, Threaded - M30