



Omron Automation & Safety



E2A-M30KS15-WP-C2 5M

Product description	M30 SHLD,NPB,15MM,NPN,NC,5M CA
RoHs Status	Lead free / RoHS Compliant
Stock Condition	1037 pcs stock
Ship From	Hong Kong
Shipment Way	DHL/Fedex/TNT/UPS/EMS

Specifications of E2A-M30KS15-WP-C2 5M

PART NUMBER	E2A-M30KS15-WP-C2 5M
MANUFACTURER	Omron Automation & Safety
DESCRIPTION	M30 SHLD,NPB,15MM,NPN,NC,5M CA
LEAD FREE STATUS / ROHS STATUS	Lead free / RoHS Compliant
QUANTITY AVAILABLE	1037 pcs
DATA SHEET	
VOLTAGE - SUPPLY	10 V ~ 32 V
TERMINATION STYLE	Cable Leads
SHIELDING	Shielded
SERIES	E2A
SENSOR TYPE	Inductive
SENSING DISTANCE	0.591" (15mm)
RESPONSE FREQUENCY	250Hz
PACKAGE / CASE	Cylinder, Threaded - M30
OUTPUT TYPE	NPN-NC, 3-Wire
OTHER NAMES	E2A-M30KS15-WP-C2 5M-ND E2A-M30KS15-WP-C25M E2AM30KS15WPC25M
OPERATING TEMPERATURE	-40°C ~ 70°C
MOISTURE SENSITIVITY LEVEL (MSL)	1 (Unlimited)
MATERIAL - BODY	Nickel-Plated Brass
LEAD FREE STATUS / ROHS STATUS	Lead free / RoHS Compliant
INGRESS PROTECTION	IP67, IP69K
INDICATOR	LED
DETAILED DESCRIPTION	Inductive Proximity Sensor 0.591" (15mm) IP67, IP69K Cylinder, Threaded - M30