



Omron Automation & Safety



E2A-M30LN30-WP-B2 2M

Penerangan Produk	M30LNG UNSH,NPB,30MM,PNP,NC,2M
Status RoHS	Memimpin percuma / RoHS Compliant
Keadaan Stok	793 pcs stock
Kapal Dari	Hong Kong
Cara Penghantaran	DHL/Fedex/TNT/UPS/EMS

Spesifikasi E2A-M30LN30-WP-B2 2M

NOMBOR BAHAGIAN	E2A-M30LN30-WP-B2 2M
PENGELUAR	Omron Automation & Safety
PENERANGAN	M30LNG UNSH,NPB,30MM,PNP,NC,2M
STATUS STATUS PERCUMA / ROSH STATUS	Memimpin percuma / RoHS Compliant
KUANTITI TERSEDIA	793 pcs
LEMBARAN DATA	
VOLTAN - BEKALAN	10 V ~ 32 V
STYLE PENAMATAN	Cable Leads
PERISAI	Unshielded
SIRI	E2A
JENIS SENSOR	Inductive
SENSING JARAK	1.181" (30mm)
RESPON FREKUENSI	100Hz
PAKEJ / KES	Cylinder, Threaded - M30
JENIS OUTPUT	PNP-NC, 3-Wire
NAMA LAIN	E2A-M30LN30-WP-B2 2M-ND E2A-M30LN30-WP-B22M E2AM30LN30WPB22M
SUHU OPERASI	-40°C ~ 70°C
TAHAP SENSITIVITI LEMBAPAN (MSL)	1 (Unlimited)
BAHAN - BADAN	Nickel-Plated Brass
STATUS STATUS PERCUMA / ROSH STATUS	Lead free / RoHS Compliant
PERLINDUNGAN INGRESS	IP67, IP69K
PETUNJUK	LED
PENERANGAN TERPERINCI	Inductive Proximity Sensor 1.181" (30mm) IP67, IP69K Cylinder, Threaded - M30