



Omron Automation & Safety



E2A-M30LN30-WP-C1 5M

Product description	M30LNG UNSH,NPB,30MM,NPN,NO,5M
RoHs Status	Lead free / RoHS Compliant
Stock Condition	863 pcs stock
Ship From	Hong Kong
Shipment Way	DHL/Fedex/TNT/UPS/EMS

Specifications of E2A-M30LN30-WP-C1 5M

PART NUMBER	E2A-M30LN30-WP-C1 5M
MANUFACTURER	Omron Automation & Safety
DESCRIPTION	M30LNG UNSH,NPB,30MM,NPN,NO,5M
LEAD FREE STATUS / ROHS STATUS	Lead free / RoHS Compliant
QUANTITY AVAILABLE	863 pcs
DATA SHEET	
VOLTAGE - SUPPLY	10 V ~ 32 V
TERMINATION STYLE	Cable Leads
SHIELDING	Unshielded
SERIES	E2A
SENSOR TYPE	Inductive
SENSING DISTANCE	1.181" (30mm)
RESPONSE FREQUENCY	100Hz
PACKAGE / CASE	Cylinder, Threaded - M30
OUTPUT TYPE	NPN-NO, 3-Wire
OTHER NAMES	E2A-M30LN30-WP-C1 5M-ND E2A-M30LN30-WP-C15M E2AM30LN30WPC15M
OPERATING TEMPERATURE	-40°C ~ 70°C
MOISTURE SENSITIVITY LEVEL (MSL)	1 (Unlimited)
MATERIAL - BODY	Nickel-Plated Brass
LEAD FREE STATUS / ROHS STATUS	Lead free / RoHS Compliant
INGRESS PROTECTION	IP67, IP69K
INDICATOR	LED
DETAILED DESCRIPTION	Inductive Proximity Sensor 1.181" (30mm) IP67, IP69K Cylinder, Threaded - M30