

E2A-M30LS15-WP-B1 2M

Penerangan Produk	SENS PROX M30 15MM PNP-NO SHILD
Status RoHS	Memimpin percuma / RoHS Compliant
Kadaan Stok	1022 pcs stock
Kapal Dari	Hong Kong
Cara Penghantaran	DHL/Fedex/TNT/UPS/EMS



Spesifikasi E2A-M30LS15-WP-B1 2M

NOMBOR BAHAGIAN	E2A-M30LS15-WP-B1 2M
PENGELUAR	Omron Automation & Safety
PENERANGAN	SENS PROX M30 15MM PNP-NO SHILD
STATUS STATUS PERCUMA / ROSH STATUS	Memimpin percuma / RoHS Compliant
KUANTITI TERSEDIA	1022 pcs
LEMBARAN DATA	
VOLTAN - BEKALAN	10 V ~ 32 V
STYLE PENAMATAN	Cable Leads
PERISAI	Shielded
SIRI	E2A
JENIS SENSOR	Inductive
SENSING JARAK	0.591" (15mm)
RESPON FREKUENSI	250Hz
PAKEJ / KES	Cylinder, Threaded - M30
JENIS OUTPUT	PNP-NO, 3-Wire
NAMA LAIN	E2A-M30LS15-WP-B1 2M-ND E2AM30LS15WPB12M Z3429
SUHU OPERASI	-40°C ~ 70°C
TAHAP SENSITIVITI LEMBAPAN (MSL)	1 (Unlimited)
BAHAN - BADAN	Nickel-Plated Brass
STATUS STATUS PERCUMA / ROSH STATUS	Lead free / RoHS Compliant
PERLINDUNGAN INGRESS	IP67, IP69K
PETUNJUK	LED
PENERANGAN TERPERINCI	Inductive Proximity Sensor 0.591" (15mm) IP67, IP69K Cylinder, Threaded - M30