



E2A-M30LS15-WP-B1 5M

Penerangan Produk	PROXIMITY SENSOR M30 15MM PNP
Status RoHS	Memimpin percuma / RoHS Compliant
Keadaan Stok	773 pcs stock
Kapal Dari	Hong Kong
Cara Penghantaran	DHL/Fedex/TNT/UPS/EMS

Spesifikasi E2A-M30LS15-WP-B1 5M

NOMBOR BAHAGIAN	E2A-M30LS15-WP-B1 5M
PENGELUAR	Omron Automation & Safety
PENERANGAN	PROXIMITY SENSOR M30 15MM PNP
STATUS STATUS PERCUMA / ROSH STATUS	Memimpin percuma / RoHS Compliant
KUANTITI TERSEDIA	773 pcs
LEMBARAN DATA	
VOLTAN - BEKALAN	10 V ~ 32 V
STYLE PENAMATAN	Cable Leads
PERISAI	Shielded
SIRI	E2A
JENIS SENSOR	Inductive
SENSING JARAK	0.591" (15mm)
RESPON FREKUENSI	250Hz
PAKEJ / KES	Cylinder, Threaded - M30
JENIS OUTPUT	PNP-NO, 3-Wire
NAMA LAIN	E2A-M30LS15-WP-B1 5M-ND E2A-M30LS15-WP-B15M E2A/M30LS15/WP/B1 5M E2AM30LS15WPB15M
SUHU OPERASI	-40°C ~ 70°C
TAHAP SENSITIVITI LEMBAPAN (MSL)	1 (Unlimited)
BAHAN - BADAN	Nickel-Plated Brass
STATUS STATUS PERCUMA / ROSH STATUS	Lead free / RoHS Compliant
PERLINDUNGAN INGRESS	IP67, IP69K
PETUNJUK	LED
PENERANGAN TERPERINCI	Inductive Proximity Sensor 0.591" (15mm) IP67, IP69K Cylinder, Threaded - M30