



Omron Automation & Safety



E2A-M30LS15-WP-C1 2M

Product description	SENS PROX M30 15MM NPN-NO SHILD
RoHs Status	Lead free / RoHS Compliant
Stock Condition	977 pcs stock
Ship From	Hong Kong
Shipment Way	DHL/Fedex/TNT/UPS/EMS

Specifications E2A-M30LS15-WP-C1 2M

PART NUMBER	E2A-M30LS15-WP-C1 2M
MANUFACTURER	Omron Automation & Safety
DESCRIPTION	SENS PROX M30 15MM NPN-NO SHILD
LEAD FREE STATUS / ROHS STATUS	Lead free / RoHS Compliant
QUANTITY AVAILABLE	977 pcs
DATA SHEET	
VOLTAGE - SUPPLY	10 V ~ 32 V
TERMINATION STYLE	Cable Leads
SHIELDING	Shielded
SERIES	E2A
SENSOR TYPE	Inductive
SENSING DISTANCE	0.591" (15mm)
RESPONSE FREQUENCY	250Hz
PACKAGE / CASE	Cylinder, Threaded - M30
OUTPUT TYPE	NPN-NO, 3-Wire
OTHER NAMES	E2A-M30LS15-WP-C1 2M-ND E2A-M30LS15-WP-C12M E2AM30LS15WPC12M
OPERATING TEMPERATURE	-40°C ~ 70°C
MOISTURE SENSITIVITY LEVEL (MSL)	1 (Unlimited)
MATERIAL - BODY	Nickel-Plated Brass
LEAD FREE STATUS / ROHS STATUS	Lead free / RoHS Compliant
INGRESS PROTECTION	IP67, IP69K
INDICATOR	LED
DETAILED DESCRIPTION	Inductive Proximity Sensor 0.591" (15mm) IP67, IP69K Cylinder, Threaded - M30