



E2A-S08KS02-WP-B2 5M

Penerangan Produk	M8 SHLD,SS,2MM,PNP,NC,5M CABLE
Status RoHS	Lead percuma / RoHS Compliant
Kapal Dari	Hong Kong
Cara Penghantaran	DHL/Fedex/TNT/UPS/EMS

Spesifikasi E2A-S08KS02-WP-B2 5M

NOMBOR BAHAGIAN	E2A-S08KS02-WP-B2 5M
PENGELUAR	Omron Automation & Safety
PENERANGAN	M8 SHLD,SS,2MM,PNP,NC,5M CABLE
STATUS STATUS PERCUMA / ROSH STATUS	Lead percuma / RoHS Compliant
LEMBARAN DATA	
VOLTAN - BEKALAN	10 V ~ 32 V
STYLE PENAMATAN	Cable Leads
PERISAI	Shielded
SIRI	E2A
JENIS SENSOR	Inductive
SENSING JARAK	0.079" (2mm)
RESPON FREKUENSI	1.5kHz
PAKEJ / KES	Cylinder, Threaded - M8
JENIS OUTPUT	PNP-NC, 3-Wire
NAMA LAIN	E2A-S08KS02-WP-B2 5M-ND E2A-S08KS02-WP-B25M E2AS08KS02WPB25M
SUHU OPERASI	-40°C ~ 70°C
TAHAP SENSITIVITI LEMBAPAN (MSL)	1 (Unlimited)
BAHAN - BADAN	Stainless Steel
STATUS STATUS PERCUMA / ROSH STATUS	Lead free / RoHS Compliant
PERLINDUNGAN INGRESS	IP67, IP69K
PETUNJUK	LED
PENERANGAN TERPERINCI	Inductive Proximity Sensor 0.079" (2mm) IP67, IP69K Cylinder, Threaded - M8