



Omron Automation & Safety



E2A-S08LS02-WP-B1 5M

Product description	M8 LNG,SHLD,SS,2MM,PNP,NO,5M
RoHs Status	Lead free / RoHS Compliant
Stock Condition	943 pcs stock
Ship From	Hong Kong
Shipment Way	DHL/Fedex/TNT/UPS/EMS

Specifications E2A-S08LS02-WP-B1 5M

PART NUMBER	E2A-S08LS02-WP-B1 5M
MANUFACTURER	Omron Automation & Safety
DESCRIPTION	M8 LNG,SHLD,SS,2MM,PNP,NO,5M
LEAD FREE STATUS / ROHS STATUS	Lead free / RoHS Compliant
QUANTITY AVAILABLE	943 pcs
DATA SHEET	
VOLTAGE - SUPPLY	10 V ~ 32 V
TERMINATION STYLE	Cable Leads
SHIELDING	Shielded
SERIES	E2A
SENSOR TYPE	Inductive
SENSING DISTANCE	0.079" (2mm)
RESPONSE FREQUENCY	1.5kHz
PACKAGE / CASE	Cylinder, Threaded - M8
OUTPUT TYPE	PNP-NO, 3-Wire
OTHER NAMES	E2A-S08LS02-WP-B1 5M-ND E2A-S08LS02-WP-B15M E2AS08LS02WPB15M
OPERATING TEMPERATURE	-40°C ~ 70°C
MOISTURE SENSITIVITY LEVEL (MSL)	1 (Unlimited)
MATERIAL - BODY	Stainless Steel
LEAD FREE STATUS / ROHS STATUS	Lead free / RoHS Compliant
INGRESS PROTECTION	IP67, IP69K
INDICATOR	LED
DETAILED DESCRIPTION	Inductive Proximity Sensor 0.079" (2mm) IP67, IP69K Cylinder, Threaded - M8