

Reflectors for photoelectric sensors


E39-R

The E39-R series of reflectors for photoelectric sensors features a wide range of models with different sizes, shapes, mounting types and materials. The reflectors provide high accuracy, reflectivity and lifetime for standard applications as well as for challenging environments.


- Standard reflectors with different sizes and shapes
- Detergent and heat resistant reflectors
- Screw mounting, snap-in or self-adhesive types




Ordering information

Shape	Type	Housing material	Features	Size in mm	Applicable Sensor	Order code	
	General purpose reflectors	ABS base Acrylic surface	Surface screw mounting (diagonal holes)	40×60×7.5	Retro-reflective photoelectric sensors – without M.S.R. Retro-reflective photoelectric sensors – with M.S.R.*1	E39-R1S	
			Surface screw mounting (holes on one side only)	35.4×42.3×8		E39-R9	
				51.4×60.3×8.5		E39-R42	
	Small size		Side screw mounting or surface selfadhesive	41.8×22.5×11		Retro-reflective photoelectric sensors – without M.S.R. Retro-reflective photoelectric sensors – with M.S.R.*1	E39-R3
				23×13.7×4.9			E39-R4
	Large size		Surface screw mounting	100×100×9			E39-R8
				84.5×84.5×8.7			E39-R40

*1 Mirror Surface Rejection (MSR) is realized by using polarization filters

Shape	Type	Housing material	Features	Size in mm	Applicable Sensor	Order code
	High precision	ABS base Acrylic surface	Microtripel for improved performance with fine beam sensors	52×40×4.8	Recommended for fine beam coaxial models (E3C-LR, E3Z-LR, E3T-SR4)	E39-R6
				30×45		E39-R12
				14×23×1		E39-R37-CA
				12×24		E39-R13
	Simple mounting	ABS base Acrylic surface	Round shape with centered mounting hole for simple screw mounting	Diameter: 84 Depth: 7.4	Photoelectric sensors with and without M.S.R. ^{*1}	E39-R7
	Snap mounting		Snap mounting for fast installation	Diameter: 30 Diameter of snap mount tool: 5	Recommended for snap mounting sensor E3FZ	E39-R49
	Enhanced detergent resistance	PVC	Surface screw mounting IP69k after DIN 40050 part 9	40×60×7.5	Recommended for harsh environment sensors	E39-R50
				20×60×6		E39-R51
	Highest detergent resistance	SUS316L Borosilicat	Surface screw mounting	43×30×5		E39-R16
	Heat resistant	Borosilicat	Surface screw mounting 450°C heat resistance Suitable for vacuum environment	95×51×8		E39-R47
	Non-fogging reflector	ABS Acrylic surface	Anti-fogging coating	40×60×7.5		E39-R1K

^{*1} Mirror Surface Rejection (MSR) is realized by using polarization filters

Shape	Type	Housing material	Features	Size in mm	Applicable Sensor	Order code
	Special polarizing	ABS base PMMA surface	Special polarizing filter to PET	40×80×8.5	E3ZM-B	E39-RP1
	General purpose tape reflectors	Acrylic	Self adhesive Pre cut	35×10×0.7	Photoelectric sensors with and without M.S.R.*1	E39-RS1
				40×35×0.7	Optimised for E3T-SR4	E39-RS1-CA
				80×70×0.6	Optimised for E3T-SR4	E39-RS2
			Self adhesive Self cut/roll material	25 mm × 5 m	Optimised for E3T-SR4	E39-RS2-CA
				25 mm × 22.8 m		E39-RS3
				50 mm × 5 m		E39-RS3-CA
				50 mm × 22.8 m		
			High precision tape reflectors	Self adhesive Pre cut	195×22	Recommended for fine beam and laser sensors (E3Z-LR, E3C, E3X)
	108×46	E39-RS5				

*1 Mirror Surface Rejection (MSR) is realized by using polarization filters