



Changeover switch, With thumb-grip, momentary, 2 NC, Cable (black) with non-terminated end, 4 pole, 3.5 m, 2 positions, Bezel: titanium

**Referencia
Catalog No.**

**C22-WK-K02-P65
186174**

Delivery program

Product range			RMQ compact solution
Basic function			Selector switch actuators
Mounting hole diameter	Ø	mm	22.5
Single unit/Complete unit			Complete unit
Design			With thumb-grip
			momentary
Function:			
			40°
Connection type			Cable (black) with non-terminated end, 4 pole
Cable Length		m	3.5
			2 positions
Degree of Protection			IP66 (front) IP65 (on rear)
Front ring			Bezel: titanium
Connection to SmartWire-DT			no
Contacts			
N/C = Normally closed			2 NC
Notes			= safety function, by positive opening to IEC/EN 60947-5-1
Actuator travel and actuation force as per DIN EN 60947-5-1, K.5.4.1			
	mm		4.65
Maximum travel	mm		5.7
Minimum force for positive opening	N		30
Contact sequence			BN WH BK BU
Contact travel = Contact closed = Contact open			
Contact diagram			 Zw = 4.5 mm

Technical data

General

Standards			IEC/EN 60947-5-1 VDE 0660
Certifications			CE, UL, CSA
Operating frequency	Operations/h		≤ 2000
Operating torque		Nm	≤ 0.3
Tightening torque Threaded ring		Nm	2

Climatic proofing			Damp heat, constant, to IEC 60068-2-78 Damp heat, cyclic, to IEC 60068-2-30
Degree of Protection			IP66 (front) IP65 (on rear)
Ambient temperature			
Open		°C	-30 - +70
Storage		°C	- 30 - + 80
Mounting position			As required
Mechanical shock resistance, shock duration 11 ms		g	> 30

Contacts

Rated impulse withstand voltage	U _{imp}	V AC	800
Rated insulation voltage	U _i	V	30
Overtoltage category/pollution degree			III/3
Control circuit reliability			
At 17 V DC/7 mA	H _F		N/C contact: statistically determined 1 failure per 0.9 × 10 ⁶ Operations
Max. short-circuit protective device			
Fuse	gG/gL	A	4
Rated conditional short-circuit current	I _q	kA	1

Switching capacity

Rated operational current	I _e	A	
AC-15			
24 V	I _e	A	4
DC-13			
24 V	I _e	A	3

Cable characteristics

Design			Cable end open
Cable Length		m	3.5
Material characteristic			PUR
Diameter	Ø	mm	4.7

Design verification as per IEC/EN 61439

Datos técnicos para la verificación del diseño			
Temperatura ambiente mínima de funcionamiento		°C	-30
Temperatura ambiente máxima de funcionamiento		°C	70

Technical data ETIM 7.0

Conmutadores en baja tensión (EG000017) / Interruptor de selección completo (incl. bloque de contactos) (EC001029)			
Tecnología electrónica, de automatización y de mando de procesos / Tecnología de conmutación de baja tensión / Equipo de comando y señalización / Equipo de comando y señalización completo (para montaje) (ecl@ss10.0.1-27-37-12-43 [ACN984011])			
Número de posiciones de conmutación			2
Tipo de elemento de control			Intercambio
Apto para iluminación			No
Con lámpara			No
Botón de color			Negro
Diámetro de orificio		Millimeter	22.5
Anchura de apertura		Millimeter	0
Altura métrica de la apertura		Millimeter	0
Mecanismo de enganche de la función de conmutación			No
Retorno de resorte			Sí
Grado de protección (IP)			Otros
Intervalo de alimentación		Volt	0 - 0
Número de contactos como contacto normalmente abierto			0
Número de contactos como contacto normalmente cerrado			2
Número de contactos como contacto de intercambio			0
Tipo de conexión de eléctrica			Otros
Con anillo central			Sí

Material de anillo frontal			Plástico
Anillo delantero, color			Otros

Approvals

Product Standards			IEC/EN 60947-5-1; UL 508; CAN/CSA-C22.2 No. 14-18 and No. 94.2-15; CE marking
UL File No.			E29184
UL Category Control No.			NKCR
CSA File No.			165628
CSA Class No.			321103
North America Certification			UL listed, CSA certified

Dimensions

