




LED element, green, front mount, cage clamp


Part no. **M22-CLED-G**
Article no. **216571**
Catalog No. **M22-CLED-GQ**

Delivery programme

| | | | |
|---|------------|----|---|
| Product range | | | RMQ-Titan (drilling dimensions 22.5 mm) |
| Basic function | | | LED elements |
| Single unit/Complete unit | | | Single unit |
| Description | | | Cage Clamp is a registered trademark of Wago Kontakttechnik GmbH/Minden, Germany |
| Fixing | | | Front fixing |
| Connection technique | | | Cage Clamp |
| Rated operational voltage | U_e | V | 12 - 30 V AC/DC, 50/60 Hz |
| Rated operational current | I_e | mA | 8 - 15 |
| Power consumption | $P_{max.}$ | W | 0.26 |
| | | | at 24 V |
| Colour | | | |
| | | |  |
| | | | Green |
| Degree of Protection | | | IP20 |
| Connection to SmartWire-DT | | | no |
| Notes | | | |
| Bei Leuchtmeldern, Leuchtdrucktasten und Leuchtwahltasten gilt: | | | |
| M22...-R nur in Kombination mit M22-LED...-R | | | |
| M22...-G nur in Kombination mit M22-LED...-G | | | |
| M22...-W nur in Kombination mit M22-LED...-W | | | |
| M22...-Y nur in Kombination mit M22-LED...-W | | | |
| M22...-B in Kombination mit M22-LED...-W oder M22-LED...-B | | | |

Technical data

General

| | | | |
|------------------------------------|--|-----------------|---|
| Standards | | | IEC/EN 60947 VDE 0660 |
| Operating torque (screw terminals) | | Nm |  0.8 |
| Climatic proofing | | | Damp heat, constant, to IEC 60068-2-78 Damp heat, cyclic, to IEC 60068-2-30 |
| Ambient temperature | | | |
| Open | | °C | -25 - +70 |
| Storage | | °C | - 40 - + 80 |
| Mounting position | | | As required |
| Mechanical shock resistance | | g | 30 Shock duration 11 ms Sinusoidal according to IEC 60068-2-27 |
| Terminal capacities | | mm ² | |
| Solid | | mm ² | 0.75 - 2.5 |

| | | | |
|---|------------------|-----------------|-----------|
| Stranded | | mm ² | 0.5 - 2.5 |
| Contacts | | | |
| Rated impulse withstand voltage | U _{imp} | V AC | 6000 |
| Rated insulation voltage | U _i | V | 500 |
| Overvoltage category/pollution degree | | | III/3 |
| Indoor and protected outdoor installation | | | |

Design verification as per IEC/EN 61439

| | | | |
|--|-------------------|----|--|
| Technical data for design verification | | | |
| Rated operational current for specified heat dissipation | I _n | A | 0 |
| Heat dissipation per pole, current-dependent | P _{vid} | W | 0 |
| Equipment heat dissipation, current-dependent | P _{vid} | W | 0 |
| Static heat dissipation, non-current-dependent | P _{vs} | W | 0.45 |
| Heat dissipation capacity | P _{diss} | W | 0 |
| Operating ambient temperature min. | | °C | -25 |
| Operating ambient temperature max. | | °C | 70 |
| IEC/EN 61439 design verification | | | |
| 10.2 Strength of materials and parts | | | |
| 10.2.2 Corrosion resistance | | | Meets the product standard's requirements. |
| 10.2.3.1 Verification of thermal stability of enclosures | | | Meets the product standard's requirements. |
| 10.2.3.2 Verification of resistance of insulating materials to normal heat | | | Meets the product standard's requirements. |
| 10.2.3.3 Verification of resistance of insulating materials to abnormal heat and fire due to internal electric effects | | | Meets the product standard's requirements. |
| 10.2.4 Resistance to ultra-violet (UV) radiation | | | Meets the product standard's requirements. |
| 10.2.5 Lifting | | | Does not apply, since the entire switchgear needs to be evaluated. |
| 10.2.6 Mechanical impact | | | Does not apply, since the entire switchgear needs to be evaluated. |
| 10.2.7 Inscriptions | | | Meets the product standard's requirements. |
| 10.3 Degree of protection of ASSEMBLIES | | | Does not apply, since the entire switchgear needs to be evaluated. |
| 10.4 Clearances and creepage distances | | | Meets the product standard's requirements. |
| 10.5 Protection against electric shock | | | Does not apply, since the entire switchgear needs to be evaluated. |
| 10.6 Incorporation of switching devices and components | | | Does not apply, since the entire switchgear needs to be evaluated. |
| 10.7 Internal electrical circuits and connections | | | Is the panel builder's responsibility. |
| 10.8 Connections for external conductors | | | Is the panel builder's responsibility. |
| 10.9 Insulation properties | | | |
| 10.9.2 Power-frequency electric strength | | | Is the panel builder's responsibility. |
| 10.9.3 Impulse withstand voltage | | | Is the panel builder's responsibility. |
| 10.9.4 Testing of enclosures made of insulating material | | | Is the panel builder's responsibility. |
| 10.10 Temperature rise | | | The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices. |
| 10.11 Short-circuit rating | | | Is the panel builder's responsibility. The specifications for the switchgear must be observed. |
| 10.12 Electromagnetic compatibility | | | Is the panel builder's responsibility. The specifications for the switchgear must be observed. |
| 10.13 Mechanical function | | | The device meets the requirements, provided the information in the instruction leaflet (IL) is observed. |

Technical data ETIM 6.0

| | | | |
|--|--|---|---------|
| Low-voltage industrial components (EG000017) / Lamp holder block for control circuit devices (EC000204) | | | |
| Electric engineering, automation, process control engineering / Low-voltage switch technology / Command and alarm device / Bulb socket block for command and alarm devices (ecl@ss8.1-27-37-12-09 [AKF027011]) | | | |
| With integrated transformer | | | No |
| With integrated voltage decreasing resistor | | | No |
| With integrated lamp | | | Yes |
| With integrated diode | | | Yes |
| Lamp holder | | | None |
| Rated voltage Ue at AC 50 Hz | | V | 12 - 30 |
| Rated voltage Ue at AC 60 Hz | | V | 12 - 30 |

| | | |
|-----------------------------------|---|-------------------------|
| Rated voltage Ue at DC | V | 12 - 30 |
| Voltage type for actuating | | AC/DC |
| Type of lamp | | LED |
| Connection type auxiliary circuit | | Spring clamp connection |
| Colour lamp | | Green |
| Type of fastening | | Front fastening |

Approvals

| | | |
|--|--|--|
| | | IEC/EN 60947-5; UL 508; CSA-C22.2 No. 14-05; CSA-C22.2 No. 94-91; CE marking |
| | | E29184 |
| | | NKCR |
| | | 012528 |
| | | 3211-03 |
| | | UL listed, CSA certified |
| | | UL/CSA Type: - |

Dimensions

The technical drawing shows two views of a pushbutton. The front view on the left shows a rectangular button with three vertical columns of terminals. The width of each column is 10 units, and the total width is 30 units. The side view on the right shows the button's profile with a height dimension 'A' and two width dimensions: 45 units for the main body and 71 units for the total width including the terminal block.

A = 39

Pushbutton with M22-(C)K...
Pushbutton with M22-(C) LED... + M22-XLED...

Additional product information (links)

| | |
|---|---|
| IL04716002Z (AWA1160-1745) RMQ-Titan System | |
| IL04716002Z (AWA1160-1745) RMQ-Titan System | ftp://ftp.moeller.net/DOCUMENTATION/AWA_INSTRUCTIONS/IL04716002Z2015_02.pdf |