



## EE-SX674

Photo micro sensor, slot type, Close-mounting, L-ON/D-ON selectable, NPN, connector

# Specifications

|                           |                        |
|---------------------------|------------------------|
| Shape                     | Close-mounting         |
| Sensing method            | Through-beam with slot |
| Sensing distance          | 5 mm                   |
| Setting method            | Fixed                  |
| Connection method         | System connector       |
| Output type               | NPN                    |
| Operation mode            | Dark-ON, Light-ON      |
| Response time             | 0.17 ms                |
| Material housing          | PBT                    |
| Thread size               | Other                  |
| Product Width (unpacked)  | 13.6 mm                |
| Product Height (unpacked) | 15.5 mm                |
| Product Depth (unpacked)  | 25.3 mm                |
| Type of light             | Infrared light         |
| Power supply voltage      | 5-24 V                 |

## Accessories



**EE-1001**

Accessory Connector for Photomicrosensors, 4-pin , solder terminals



**EE-1001-1**

Connector for Photomicrosensors, 4-pin , solder terminals, bridge between L and +



**EE-1006 1M**

Accessory Photomicro sensor connector with cable 1 m



**EE-1006 2M**

Accessory Photomicro sensor connector with cable 2 m



**EE-1006 3M**

Accessory Photomicro sensor connector with cable 3m



**EE-1010 2M**

Accessory Photomicro sensor EE-SPX\_03, cable connector, PVC, 2m



**EE-1010-R 2M**

Accessory photomicro sensor EE-SPX\_03, cable connector, robotic PVC, 2 m

## Downloads

**CAD Library**



**EE-series  
Photomicrosensors  
Datasheet**

**EN** PDF 9.35 MB

