

A9 – A/AE75 , EK110 – EK1000, AL9 – AL26

AC & DC operated


UL rated, 4 pole

Across the line


1



A9-40-00



A75-40-00



EK175C4P-PL

4 Pole – 4 NO power poles

UL general purpose current		AC operated		DC operated	
AC operated	DC operated	Catalog number	List price	Catalog number	List price
21	21	A9-40-00-84		AL9-40-00-81	
30	30	A16-40-00-84		AL16-40-00-81	
40	40	A26-40-00-84		AL26-40-00-81	
65	65	A45-40-00-84		AE45-40-00-86	
80	80	A50-40-00-84		AE50-40-00-86	
105	105	A75-40-00-84		AE75-40-00-86	
150	150	EK110C4P-1L		EK110C4P-PL	
200	200	EK150C4P-1L		EK150C4P-PL	
250	250	EK175C4P-1L		EK175C4P-PL	
300	300	EK210C4P-1L		EK210C4P-PL	
400	400	EK370C4P-1L		EK370C4P-PL	
600	600	EK550C4P-1L		EK550C4P-PL	
1000 ①	1000 ①	EK1000C4P-1L		EK1000C4P-PL	

4 Pole – 4 NC power poles

UL general purpose current	AC operated	
AC operated	Catalog number	List price
30	A16-04-00-84	

4 Pole – 2 NO & 2 NC power poles

UL general purpose current		AC operated		DC operated	
AC operated	DC operated	Catalog number	List price	Catalog number	List price
21	21	A9-22-00-84		AL9-22-00-81	
30	21	A16-22-00-84		AL16-22-00-81	
40	30	A26-22-00-84		AL26-22-00-81	
65	65	A45-22-00-84		AE45-22-00-86	
105	105	A75-22-00-84		AE75-22-00-86	

Coil voltage selection

All AC operated catalog numbers include a 120VAC coil. All DC operated catalog numbers include a 110VDC coil. To select other coil voltages, substitute the code from the Coil Voltage Selection Chart for the two digits after the last dash in the catalog number.

Ex.: A 240V coil is required for an A75 contactor: A75-30-00-**80**

Auxiliary contact blocks

For additional auxiliary contact blocks, see catalog number explanation on page 1.2. Add \$ 20 to list price for each additional auxiliary, and see page 1.18 for available combinations.

Accessories for EK

Please consult factory.

Coil voltage selection – A contactors

Hz	Cntr	Volts															
		type	12	24	48	110	120	125	208	220	240	277	380	415	440	480	500
60	A		81	83	84	84		34	36	80	42		86	86	51	53	55
50	A		81	83	84				80			85	86			55	

For other voltages, see page 1.26.

Coil voltage selection – EK contactors

Hz	Contr.	Volts														
		type	24	48	110	120	125	208	220	240	277	380	415	440	480	500
60	EK	F	G		1		B		2	C	Z		3	4		6
50	EK	N		1				J			3	M			5	
DC	EK	Y	W	P		Q		R					T			

• For other voltages, consult factory.

• 24 & 48VAC coils are not available for sizes EK550. For these applications, use an interposing control relay.

Coil voltage selection – AE & AL contactors

Hz	Contr. type	Volts						
		12	24	48	110	125	220	240
DC	AE, AL	—	81	83	86	87	88	89

For other voltages, see page 1.26.