



PRODUCT-DETAILS

EOT16U3M1-1S

EOT16U3M1-1S Enclosed Disconnect Switch



General Information	
Extended Product Type	EOT16U3M1-1S
Product ID	1SCA022823R6800
EAN	6417019282213
Catalog Description	EOT16U3M1-1S Enclosed Disconnect Switch
Long Description	Enclosed Switch Disconnecter, 3-p. Max. Horse power rating at three phase 480V 10HP. General purpose current rating 16A. Steel sheet enclosure, NEMA Type 1 Indoor, Selector handle. Interlocked cover. Defeatable interlocking.

Popular Downloads	
Data Sheet, Technical Information	1SCC340016C0201
Instructions and Manuals	1SCC340019M0202
Mechanical Drawings	EOTK211383S25.igs

Environmental

Degree of Protection	acc. to IEC 60529 IP30
Pollution Degree	3

Ordering

Minimum Order Quantity	1 piece
Customs Tariff Number	85365080
Country of Origin	Mexico (MX)

Dimensions

Product Net Width	134.1 mm 5.28 in
Product Net Height	215.9 mm 8.5 in
Product Net Depth / Length	83.3 mm 3.28 in
Product Net Weight	2.1 kg 4.63 lb

Container Information

Package Level 1 Units	1 piece
Package Level 1 Width	165 mm
Package Level 1 Depth / Length	227 mm
Package Level 1 Height	142 mm
Package Level 1 Gross Weight	2.1 kg 4.63 lb
Package Level 1 EAN	6417019282213

Technical

Cable Entry Position	Up/Down
Cable Outlets Per Side	2x(ø1 / 25.4+ø0.75 / 19.1)
Connecting Capacity	Screw Clamp 0.75 ... 10 mm²
Main Circuit	Screw Clamp / PE Terminal 1pcs, 0.5 ... 16 mm²
Conventional Thermal Current (I _{the})	16 A
Degree of Protection	acc. to IEC 60529 IP30
Enclosure Material	Steel sheet
Enclosure Type	NEMA Type 1 Indoor
Handle Color	Black
Handle Type	Selector handle
Mechanical Durability	20000
Mounted Auxiliary Contacts	1 NO, 0 NC
Number of Poles	3P
Pollution Degree	3
Position of Line Terminals	Top In - Bottom Out
Rated Insulation Voltage (U _i)	acc. to IEC/EN 60664-1 750 V
Rated Operational Voltage	Main Circuit 750 V

Standards	UL 508
Terminal Type	Screw Terminals

Technical UL/CSA

Maximum Operating Voltage UL/CSA	600 V
Ampere Rating	16 A
Horsepower Rating UL/CSA	(220 ... 240 V AC) Three Phase 5 Hp (480 V AC) 10 Hp (600 V AC) 10 Hp
Tightening Torque UL/CSA	Main Circuit 7 in·lb

External Classifications and Standards

Object Classification Code	Q
ETIM 8	EC000216 - Switch disconnect
UNSPSC	39122233
IDEA Granular Category Code (IGCC)	5290 >> Disconnect switch
eClass	V11.1 : 27371403
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

Categories

Low Voltage Products and Systems → Enclosed Switches → Enclosed Disconnect Switches

