


Adaptor Shoes and Accessories

Illustration	Adaptor Shoes Provide mechanical mounting and electrical power connection to busbar system.	Width	Length	For use with Device Type	Catalog No	Price \$
 FBS2545	With wire: 25 amp rated (12AWG)	45 mm	182 mm	3RV101, 3RV102	FBS2545	39.
	With wire: 32 amp rated (10AWG)	54 mm	182 mm	3VU13	FBS3254	46.
		72 mm	182 mm	3VU16	FBS3272	54.
	With wire: 65 amp rated (8AWG)	72 mm	182 mm	3VU16	FBS6572	54.
	With wire: 50 amp rated	55 mm	185 mm	3RV103	FBS5055	54.
55 mm		242 mm	FBS5055L		54.	
 FBS0045	With terminals for wire size #10-#6: 80 amp rated	72 mm	182 mm	FBCB15-80	FBS8072	77.
	With wire: 100 amp rated	70 mm	182 mm	3RV104	FBS10070	102.
	With terminals for wire #4-2/0 Includes mounting plate for mounting E or F frame breakers Rated 250 amps (terminals on top of shoe)	108 mm	270 mm	FBCB	FBS250108	282.
		With terminals for wire #4-2/0 Includes mounting plate for mounting E or F frame breakers Rated 250 amps (terminals on bottom of shoe)	108 mm	270 mm	FBCB	FBS250108M
	Without wire: For mechanical mounting only Contactor Support		45 mm	182mm	3RV101	FBS0045
		55 mm	185 mm	3RV102	FBS0055	34.
		54 mm	182 mm	3VU13	FBS0054	34.
55 mm		242 mm	3RV103	FBS0055L	45.	
 8US1998-2BM00	<b>Support Bracket for 3RT104 Contactor</b> For use with FBS10070	70 mm	—	3RT104	FBS0070B	23.
	Side module for Adaptor Shoe expansion	10 mm	182 mm	—	8US1998-2BM00	12.
 FBC20	<b>Feeder Breaker Mounting Plate</b> For mounting 3-pole E-frame Siemens circuit breakers through 80 amps. Mounts to FBS8072 Adaptor Shoe.	72 mm	160 mm	FBCB15-80	FBP80	49.
	<b>3TF46/47 Mounting Plate</b> Requires (2) FBS0054 shoes and (1) FBC20	108 mm	147 mm	3TF46/47	FBT46	35.
 8US1998-1BA00	<b>Fast Clips</b> For fastening 2 or more shoes together. 2 required per pair of shoes. 20 per bag.	—	—	—	FBC20	9.
	<b>Spacer</b> For supporting a 3RT101 or 3RT102 contactor to a Fastbus shoe when used with a 3RV MSP. 1 required per contactor. (100 per bag)	—	—	—	8US1998-1BA00	78.