


EconoDUAL™3 module with TRENCHSTOP™ IGBT7 and emitter controlled 7 diode and NTC**Features**

- Electrical features
 - $V_{CES} = 1200\text{ V}$
 - $I_{C\text{ nom}} = 900\text{ A} / I_{CRM} = 1800\text{ A}$
 - Integrated temperature sensor
 - TRENCHSTOP™ IGBT7
 - $V_{CE,sat}$ with positive temperature coefficient
- Mechanical features
 - High power density
 - Isolated base plate
 - PressFIT contact technology
 - Standard housing
 - Direct-cooled base plate

**Potential applications**

- High-power converters
- Motor drives
- Servo drives
- UPS systems
- Commercial agriculture vehicles

Product validation

- Qualified for industrial applications according to the relevant tests of IEC 60747, 60749 and 60068


Description

Table of contents

	Description	1
	Features	1
	Potential applications	1
	Product validation	1
	Table of contents	2
1	Package	3
2	IGBT, Inverter	3
3	Diode, Inverter	5
4	NTC-Thermistor	6
5	Characteristics diagrams	7
6	Circuit diagram	12
7	Package outlines	13
8	Module label code	14
	Revision history	15
	Disclaimer	16

1 Package

Table 1 Insulation coordination

Parameter	Symbol	Note or test condition	Values	Unit
Isolation test voltage	V_{ISOL}	RMS, $f = 50 \text{ Hz}$, $t = 60 \text{ s}$	3.4	kV
Material of module baseplate			Cu	
Internal isolation		basic insulation (class 1, IEC 61140)	Al_2O_3	
Creepage distance	d_{Creep}	terminal to heatsink	15.0	mm
Creepage distance	d_{Creep}	terminal to terminal	13.0	mm
Clearance	d_{Clear}	terminal to heatsink	12.5	mm
Clearance	d_{Clear}	terminal to terminal	10.0	mm
Comparative tracking index	CTI		> 200	
Relative thermal index (electrical)	RTI	housing	140	°C

Table 2 Characteristic values

Parameter	Symbol	Note or test condition	Values			Unit
			Min.	Typ.	Max.	
Pressure drop in cooling circuit	Δp	$\Delta V/\Delta t = 10.0 \text{ dm}^3/\text{min}$, 50% water / 50% ethylenglycol, $T_F = 60 \text{ °C}$		65		mbar
Maximum pressure in cooling circuit	p				3	bar
Stray inductance module	L_{sCE}			20		nH
Module lead resistance, terminals - chip	$R_{\text{CC'+EE'}}$	$T_F = 25 \text{ °C}$, per switch		0.8		mΩ
Storage temperature	T_{stg}		-40		125	°C
Mounting torque for module mounting	M	- Mounting according to valid application note	M5, Screw	3	6	Nm
Terminal connection torque	M	- Mounting according to valid application note	M6, Screw	3	6	Nm
Weight	G			345		g

2 IGBT, Inverter

Table 3 Maximum rated values

Parameter	Symbol	Note or test condition		Values	Unit
Collector-emitter voltage	V_{CES}		$T_{\text{vj}} = 25 \text{ °C}$	1200	V
Continuous DC collector current	I_{CDC}	$T_{\text{vj max}} = 175 \text{ °C}$	$T_F = 25 \text{ °C}$	890	A

Table 3 (continued) Maximum rated values

Parameter	Symbol	Note or test condition	Values	Unit
Maximum RMS module DC-terminal current	I_{tRMS}		$T_{\text{Terminal}} = 90\text{ °C}$, $T_{\text{C}} = 90\text{ °C}$	A
			$T_{\text{Terminal}} = 105\text{ °C}$, $T_{\text{C}} = 90\text{ °C}$	
Repetitive peak collector current	I_{CRM}	t_{p} limited by $T_{\text{vj op}}$	1800	A
Gate-emitter peak voltage	V_{GES}		±20	V

Table 4 Characteristic values

Parameter	Symbol	Note or test condition	Values			Unit
			Min.	Typ.	Max.	
Collector-emitter saturation voltage	$V_{\text{CE sat}}$	$I_{\text{C}} = 900\text{ A}$, $V_{\text{GE}} = 15\text{ V}$	$T_{\text{vj}} = 25\text{ °C}$	1.50	1.80	V
			$T_{\text{vj}} = 125\text{ °C}$	1.65		
			$T_{\text{vj}} = 175\text{ °C}$	1.75		
Gate threshold voltage	V_{GEth}	$I_{\text{C}} = 18\text{ mA}$, $V_{\text{CE}} = V_{\text{GE}}$, $T_{\text{vj}} = 25\text{ °C}$	5.15	5.80	6.45	V
Gate charge	Q_{G}	$V_{\text{GE}} = \pm 15\text{ V}$, $V_{\text{CE}} = 600\text{ V}$		14.3		μC
Internal gate resistor	R_{Gint}	$T_{\text{vj}} = 25\text{ °C}$		0.5		Ω
Input capacitance	C_{ies}	$f = 100\text{ kHz}$, $T_{\text{vj}} = 25\text{ °C}$, $V_{\text{CE}} = 25\text{ V}$, $V_{\text{GE}} = 0\text{ V}$		122		nF
Reverse transfer capacitance	C_{res}	$f = 100\text{ kHz}$, $T_{\text{vj}} = 25\text{ °C}$, $V_{\text{CE}} = 25\text{ V}$, $V_{\text{GE}} = 0\text{ V}$		0.72		nF
Collector-emitter cut-off current	I_{CES}	$V_{\text{CE}} = 1200\text{ V}$, $V_{\text{GE}} = 0\text{ V}$, $T_{\text{vj}} = 25\text{ °C}$			0.1	mA
Gate-emitter leakage current	I_{GES}	$V_{\text{CE}} = 0\text{ V}$, $V_{\text{GE}} = 20\text{ V}$, $T_{\text{vj}} = 25\text{ °C}$			100	nA
Turn-on delay time (inductive load)	t_{don}	$I_{\text{C}} = 900\text{ A}$, $V_{\text{CE}} = 600\text{ V}$, $V_{\text{GE}} = \pm 15\text{ V}$, $R_{\text{Gon}} = 0.51\text{ Ω}$	$T_{\text{vj}} = 25\text{ °C}$	0.410		μs
			$T_{\text{vj}} = 125\text{ °C}$	0.460		
			$T_{\text{vj}} = 175\text{ °C}$	0.490		
Rise time (inductive load)	t_{r}	$I_{\text{C}} = 900\text{ A}$, $V_{\text{CE}} = 600\text{ V}$, $V_{\text{GE}} = \pm 15\text{ V}$, $R_{\text{Gon}} = 0.51\text{ Ω}$	$T_{\text{vj}} = 25\text{ °C}$	0.100		μs
			$T_{\text{vj}} = 125\text{ °C}$	0.110		
			$T_{\text{vj}} = 175\text{ °C}$	0.120		
Turn-off delay time (inductive load)	t_{doff}	$I_{\text{C}} = 900\text{ A}$, $V_{\text{CE}} = 600\text{ V}$, $V_{\text{GE}} = \pm 15\text{ V}$, $R_{\text{Goff}} = 0.51\text{ Ω}$	$T_{\text{vj}} = 25\text{ °C}$	0.550		μs
			$T_{\text{vj}} = 125\text{ °C}$	0.630		
			$T_{\text{vj}} = 175\text{ °C}$	0.690		
Fall time (inductive load)	t_{f}	$I_{\text{C}} = 900\text{ A}$, $V_{\text{CE}} = 600\text{ V}$, $V_{\text{GE}} = \pm 15\text{ V}$, $R_{\text{Goff}} = 0.51\text{ Ω}$	$T_{\text{vj}} = 25\text{ °C}$	0.110		μs
			$T_{\text{vj}} = 125\text{ °C}$	0.230		
			$T_{\text{vj}} = 175\text{ °C}$	0.330		

(table continues...)

Table 4 (continued) Characteristic values

Parameter	Symbol	Note or test condition	Values			Unit
			Min.	Typ.	Max.	
Turn-on energy loss per pulse	E_{on}	$I_C = 900\text{ A}$, $V_{CE} = 600\text{ V}$, $L_\sigma = 25\text{ nH}$, $V_{GE} = \pm 15\text{ V}$, $R_{Gon} = 0.51\text{ }\Omega$, $di/dt = 6200\text{ A}/\mu\text{s}$ ($T_{vj} = 175\text{ }^\circ\text{C}$)	$T_{vj} = 25\text{ }^\circ\text{C}$	89		mJ
			$T_{vj} = 125\text{ }^\circ\text{C}$	138		
			$T_{vj} = 175\text{ }^\circ\text{C}$	170		
Turn-off energy loss per pulse	E_{off}	$I_C = 900\text{ A}$, $V_{CE} = 600\text{ V}$, $L_\sigma = 25\text{ nH}$, $V_{GE} = \pm 15\text{ V}$, $R_{Goff} = 0.51\text{ }\Omega$, $dv/dt = 3000\text{ V}/\mu\text{s}$ ($T_{vj} = 175\text{ }^\circ\text{C}$)	$T_{vj} = 25\text{ }^\circ\text{C}$	89		mJ
			$T_{vj} = 125\text{ }^\circ\text{C}$	130		
			$T_{vj} = 175\text{ }^\circ\text{C}$	158		
SC data	I_{SC}	$V_{GE} \leq 15\text{ V}$, $V_{CC} = 800\text{ V}$, $V_{CEmax} = V_{CES} - L_{sCE} \cdot di/dt$	$t_p \leq 8\text{ }\mu\text{s}$, $T_{vj} = 150\text{ }^\circ\text{C}$	3200		A
			$t_p \leq 6\text{ }\mu\text{s}$, $T_{vj} = 175\text{ }^\circ\text{C}$	3000		
Thermal resistance, junction to cooling fluid ¹⁾	R_{thJF}	per IGBT, $\Delta V/\Delta t = 10\text{ dm}^3/\text{min}$, cooling fluid = 50% water / 50% ethylenglycol, $T_f = 60\text{ }^\circ\text{C}$		0.0837		K/W
Temperature under switching conditions	$T_{vj\text{ op}}$		-40		175	$^\circ\text{C}$

1) Typical R_{thJF} value using the heat sink described in AN-2022-05

Note: $T_{vj\text{ op}} > 150\text{ }^\circ\text{C}$ is only allowed for operation at overload conditions. For detailed specifications please refer to AN 2018-14.

3 Diode, Inverter

Table 5 Maximum rated values

Parameter	Symbol	Note or test condition		Values	Unit
Repetitive peak reverse voltage	V_{RRM}		$T_{vj} = 25\text{ }^\circ\text{C}$	1200	V
Continuous DC forward current	I_F			900	A
Repetitive peak forward current	I_{FRM}	$t_p = 1\text{ ms}$		1800	A
I^2t - value	I^2t	$t_p = 10\text{ ms}$, $V_R = 0\text{ V}$	$T_{vj} = 125\text{ }^\circ\text{C}$	35000	A^2s
			$T_{vj} = 175\text{ }^\circ\text{C}$	30000	

Table 6 Characteristic values

Parameter	Symbol	Note or test condition	Values			Unit
			Min.	Typ.	Max.	
Forward voltage	V_F	$I_F = 900 \text{ A}$, $V_{GE} = 0 \text{ V}$	$T_{vj} = 25 \text{ °C}$	1.80	2.05	V
			$T_{vj} = 125 \text{ °C}$	1.70		
			$T_{vj} = 175 \text{ °C}$	1.65		
Peak reverse recovery current	I_{RM}	$V_R = 600 \text{ V}$, $I_F = 900 \text{ A}$, $V_{GE} = -15 \text{ V}$, $-di_F/dt = 6200 \text{ A}/\mu\text{s}$ ($T_{vj} = 175 \text{ °C}$)	$T_{vj} = 25 \text{ °C}$	389		A
			$T_{vj} = 125 \text{ °C}$	511		
			$T_{vj} = 175 \text{ °C}$	578		
Recovered charge	Q_r	$V_R = 600 \text{ V}$, $I_F = 900 \text{ A}$, $V_{GE} = -15 \text{ V}$, $-di_F/dt = 6200 \text{ A}/\mu\text{s}$ ($T_{vj} = 175 \text{ °C}$)	$T_{vj} = 25 \text{ °C}$	65		μC
			$T_{vj} = 125 \text{ °C}$	127		
			$T_{vj} = 175 \text{ °C}$	171		
Reverse recovery energy	E_{rec}	$V_R = 600 \text{ V}$, $I_F = 900 \text{ A}$, $V_{GE} = -15 \text{ V}$, $-di_F/dt = 6200 \text{ A}/\mu\text{s}$ ($T_{vj} = 175 \text{ °C}$)	$T_{vj} = 25 \text{ °C}$	29		mJ
			$T_{vj} = 125 \text{ °C}$	52		
			$T_{vj} = 175 \text{ °C}$	68		
Thermal resistance, junction to cooling fluid ¹⁾	R_{thJF}	per diode, $\Delta V/\Delta t = 10 \text{ dm}^3/\text{min}$, cooling fluid = 50% water / 50% ethylenglycol, $T_f = 60 \text{ °C}$		0.132		K/W
Temperature under switching conditions	$T_{vj \text{ op}}$		-40		175	°C

1) Typical R_{thJF} value using the heat sink described in AN-2022-05

Note: $T_{vj \text{ op}} > 150 \text{ °C}$ is only allowed for operation at overload conditions. For detailed specifications please refer to AN 2018-14.

4 NTC-Thermistor

Table 7 Characteristic values


Parameter	Symbol	Note or test condition	Values			Unit
			Min.	Typ.	Max.	
Rated resistance	R_{25}	$T_{NTC} = 25 \text{ °C}$		5		kΩ
Deviation of R_{100}	$\Delta R/R$	$T_{NTC} = 100 \text{ °C}$, $R_{100} = 493 \text{ Ω}$	-5		5	%
Power dissipation	P_{25}	$T_{NTC} = 25 \text{ °C}$			20	mW
B-value	$B_{25/50}$	$R_2 = R_{25} \exp[B_{25/50}(1/T_2 - 1/(298,15 \text{ K}))]$		3375		K
B-value	$B_{25/80}$	$R_2 = R_{25} \exp[B_{25/80}(1/T_2 - 1/(298,15 \text{ K}))]$		3411		K
B-value	$B_{25/100}$	$R_2 = R_{25} \exp[B_{25/100}(1/T_2 - 1/(298,15 \text{ K}))]$		3433		K

Note: Specification according to the valid application note.

5 Characteristics diagrams


Output characteristic (typical), IGBT, Inverter

$I_C = f(V_{CE})$
 $V_{GE} = 15 \text{ V}$




Output characteristic field (typical), IGBT, Inverter

$I_C = f(V_{CE})$
 $T_{vj} = 175^\circ\text{C}$




Transfer characteristic (typical), IGBT, Inverter

$I_C = f(V_{GE})$
 $V_{CE} = 20 \text{ V}$



Switching losses (typical), IGBT, Inverter

$E = f(I_C)$
 $R_{Goff} = 0.51 \Omega$, $R_{Gon} = 0.51 \Omega$, $V_{CE} = 600 \text{ V}$, $V_{GE} = \pm 15 \text{ V}$




5 Characteristics diagrams

Switching losses (typical), IGBT, Inverter

$$E = f(R_G)$$


$I_C = 900 \text{ A}$, $V_{CE} = 600 \text{ V}$, $V_{GE} = \pm 15 \text{ V}$



Switching times (typical), IGBT, Inverter

$$t = f(I_C)$$


$R_{Goff} = 0.51 \Omega$, $R_{Gon} = 0.51 \Omega$, $V_{CE} = 600 \text{ V}$, $V_{GE} = \pm 15 \text{ V}$, $T_{vj} = 175^\circ\text{C}$



Switching times (typical), IGBT, Inverter

$$t = f(R_G)$$


$I_C = 900 \text{ A}$, $V_{CE} = 600 \text{ V}$, $V_{GE} = \pm 15 \text{ V}$



Voltage slope (typical), IGBT, Inverter

$$dv/dt = f(R_G)$$


$I_C = 900 \text{ A}$, $V_{CE} = 600 \text{ V}$, $V_{GE} = \pm 15 \text{ V}$, $T_{vj} = 25^\circ\text{C}$



5 Characteristics diagrams


Reverse bias safe operating area (RBSOA), IGBT, Inverter

$I_C = f(V_{CE})$
 $R_{Goff} = 0.51 \, \Omega$, $V_{GE} = \pm 15 \, V$, $T_{vj} = 175 \, ^\circ C$




Capacity characteristic (typical), IGBT, Inverter

$C = f(V_{CE})$
 $f = 100 \, kHz$, $V_{GE} = 0 \, V$, $T_{vj} = 25 \, ^\circ C$




Gate charge characteristic (typical), IGBT, Inverter

$V_{GE} = f(Q_G)$
 $I_C = 900 \, A$, $T_{vj} = 25 \, ^\circ C$



Transient thermal impedance, IGBT, Inverter


$Z_{th} = f(t)$



5 Characteristics diagrams


Thermal impedance , IGBT, Inverter

$R_{thJF} = f(\Delta V/\Delta t)$



Forward characteristic (typical), Diode, Inverter


$I_F = f(V_F)$



Switching losses (typical), Diode, Inverter

$E_{rec} = f(I_F)$


$R_{Gon} = 0.51 \Omega, V_{CE} = 600 V$



Switching losses (typical), Diode, Inverter

$E_{rec} = f(R_G)$


$V_{CE} = 600 V, I_F = 900 A$



5 Characteristics diagrams


Transient thermal impedance, Diode, Inverter

$Z_{th} = f(t)$




Thermal impedance, Diode, Inverter

$R_{thJF} = f(\Delta V/\Delta t)$



Temperature characteristic (typical), NTC-Thermistor

$R = f(T_{NTC})$



6 **Circuit diagram**




Figure 1

7 Package outlines




Figure 2

8 Module label code

Module label code			
Code format	Data Matrix		Barcode Code128
Encoding	ASCII text		Code Set A
Symbol size	16x16		23 digits
Standard	IEC24720 and IEC16022		IEC8859-1
Code content	<i>Content</i>	<i>Digit</i>	<i>Example</i>
	Module serial number	1 – 5	71549
	Module material number	6 - 11	142846
	Production order number	12 - 19	55054991
	Date code (production year)	20 – 21	15
	Date code (production week)	22 – 23	30
Example			
			
71549142846550549911530		71549142846550549911530	

Figure 3

Revision history

Document revision	Date of release	Description of changes
V1.0	2020-06-09	Target datasheet
n/a	2020-09-01	Datasheet migrated to a new system with a new layout and new revision number schema: target or preliminary datasheet = 0.xy; final datasheet = 1.xy
0.10	2021-07-08	Target datasheet
1.00	2022-04-01	Final datasheet

Trademarks

All referenced product or service names and trademarks are the property of their respective owners.

Edition 2022-04-01

Published by
Infineon Technologies AG
81726 Munich, Germany

© 2022 Infineon Technologies AG
All Rights Reserved.

Do you have a question about any
aspect of this document?

Email: erratum@infineon.com

Document reference
IFX-AAJ663-003

IMPORTANT NOTICE

The information given in this document shall in no event be regarded as a guarantee of conditions or characteristics ("Beschaffenheitsgarantie").

With respect to any examples, hints or any typical values stated herein and/or any information regarding the application of the product, Infineon Technologies hereby disclaims any and all warranties and liabilities of any kind, including without limitation warranties of non-infringement of intellectual property rights of any third party.

In addition, any information given in this document is subject to customer's compliance with its obligations stated in this document and any applicable legal requirements, norms and standards concerning customer's products and any use of the product of Infineon Technologies in customer's applications.

The data contained in this document is exclusively intended for technically trained staff. It is the responsibility of customer's technical departments to evaluate the suitability of the product for the intended

WARNINGS

Due to technical requirements products may contain dangerous substances. For information on the types in question please contact your nearest Infineon Technologies office.

Except as otherwise explicitly approved by Infineon Technologies in a written document signed by authorized representatives of Infineon Technologies, Infineon Technologies' products may not be used in any applications where a failure of the product or any consequences of the use thereof can reasonably be expected to result in personal injury.