

# Mechanical interlock units



VM

## Description

The VM mechanical interlock units are designed for the interlocking of two R contactors of the same rating. The mounting between 2 contactors of a same rating doesn't affect their fixing centers or their overall dimensions.

## Ordering details

For R contactors type IOR, NOR , JOR, LOR and FOR	Rating	Fixing center mm	Type	Order code	Pkg qty	Weight (1 pce) kg
IOR...-CC, IOR...-MT, NOR...-CC, NOR...-MT, LOR	63	220	VM21/24	FPL7101403R0001	1	0.140
	125	260	VM25	FPL7401404R0001	1	0.180
	200	320	VM27	FPL8001401R0001	1	0.260
IOR...-CC, IOR...-MT, NOR...400, LOR	400 ... 500	520	VM15-SP	FPL8301401R0002	1	0.500
IOR..., LOR...800, NOR...800, FOR...1000	800 ... 1000	520	VM16	FPL8601401R0001	1	0.600
IOR...-CC, IOR...-MT	800 ... 1000	640	VM17/18	FPL8801401R0001	1	0.700
IOR, LOR, FOR	1400, 1700, 2100	640				
IOR...-CC, IOR...-MT	1400, 1700, 2100	680	VM19	FPL9001401R0001	1	0.800

Note: For special versions, please consult us:

- interlocking between contactors with N.O. + N.C. poles or with latching
- interlocking between 2 contactors of different ratings
- interlocking between 3 contactors.