



PRODUCT-DETAILS

FS401E-C20/0.03

Residual Current Circuit Breaker with Overcurrent Protection



General Information	
Extended Product Type	FS401E-C20/0.03
Product ID	2CCG001666R0001
EAN	7612271521356
Catalog Description	Residual Current Circuit Breaker with Overcurrent Protection
Long Description	Pluggable Residual Current Circuit Breaker with overcurrent Protection for the SMISSLINE TP System acc. IEC/EN/DIN EN 61009-1, EN/DIN EN 61009-2-1 Rated breaking capacity Icn 10kAType F; AP-R (high immunity) Tripping characteristic C Rated current In 13A Rated sensitivity I Δn 0.03 Rated voltage Ue 240/415VAC

Technical	
Tripping Characteristic	C
Type of Residual Current	Type A
Rated Operational Voltage	acc. to IEC 60898-1 240 V
Rated Insulation Voltage (Ui)	acc. to IEC/EN 60664-1 500 V
Rated Impulse Withstand Voltage (Uimp)	4 kV

)	
Dielectric Test Voltage	2500 V
Input Voltage Type	AC
Rated Current (I _n)	20 A
Rated Operational Current (I _e)	20 A
Rated Residual Current	30 mA
Rated Short-Circuit Capacity	6 kA
Rated Residual Breaking Capacity (I _{Δm})	6000 A
Rated Service Short-Circuit Breaking Capacity, in % of I _{cu} (I _{cs})	6 kA
Maximum Surge Current	3 kA
Rated Frequency (f)	50 ... 60 Hz
Power Loss	3 W
Contact Position Indication	Red ON / Green OFF
Energy Limiting Class	3
Electrical Endurance	10000 cycle
Mechanical Endurance	20000 cycle
Number of Protected Poles	1
Number of Poles	2P
Operating Characteristic	Instantaneous
Overvoltage Category	III
Position of Neutral Terminals	Right
Tightening Torque	2.8 N·m
Actuator Type	Toggle
Earthing Switch Type	Undelayed
Screw Terminal Type	Failsafe Bi-directional Cylinder-lift Terminal
Actuator Material	Insulation Group II, Black, Sealable
Housing Material	Insulation Group I, RAL 7035
Mounting Position	Any
Accessories Available	Yes
Connecting Capacity	Stranded 0.75 ... 35 mm ² Flexible 0.75 ... 25 mm ²
Rated Cross-Section	1 - Solid-Core 0.75 ... 35 mm ² 4 - Multi-Wired 0.75 ... 10 mm ²

Material Compliance	
RoHS Information	9AKK108469A5446
REACH Declaration	9AKK108467A9561
Conflict Minerals Reporting Template (CMRT)	9AKK108468A3363

Environmental	
Ambient Air Temperature	Operation -25 ... 60 °C
Reference Ambient Air Temperature	30 °C

Degree of Protection	IP20
Pollution Degree	2
Resistance to Vibrations	1 mm 2 ... 13.2 Hz
Environmental Information	9AKK108467A9561

Technical UL/CSA

Short-Circuit Current Rating (SCCR)	0.03 A
-------------------------------------	--------

Dimensions

Width in Number of Modular Spacings	2
Product Net Width	36 mm
Product Net Height	91 mm
Product Net Depth / Length	78 mm
Product Net Weight	200 g
Built-In Depth (t ₂)	91 mm
Dimension Diagram	9AKK108469A5765

Ordering

Package Level 1 Units	carton 1 piece
Package Level 1 Gross Weight	466 g

Certificates and Declarations

Declaration of Conformity - CE	9AKK108469A5446
--------------------------------	-----------------

Installation

Instructions and Manuals	2CCR665901B0001
--------------------------	-----------------

Popular Downloads

Data Sheet, Technical Information	9AKK107492A6192
-----------------------------------	-----------------

External Classifications and Standards

ETIM 8	EC000905 - Earth leakage circuit breaker
ETIM 9	EC000905 - Earth leakage circuit breaker
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
WEEE B2C / B2B	Business To Business
CN8	85362020

Object Classification Code	FB
Standards	IEC 61009-1 EN 61009-1 EN 61009-2-1

Accessories				
Identifier	Description	Type	Quantity	Unit Of Measure
2CCS500900R0081	HK40011-L	Auxiliary swtich	1	piece
2CCF201112R0001	HK40020-L	Auxiliary swtich	1	piece
2CCF201114R0001	HK40002-L	Auxiliary swtich	1	piece
2CCS500900R0101	SK40011-L	Signal contact	1	piece
2CCF201162R0001	SK40020-L	Signal contact	1	piece
2CCF201164R0001	SK40002-L	Signal contact	1	piece
2CCS500900R0141	SK40010-LSA	Signal contact	1	piece
2CCF201212R0001	HK40010-LSA	Auxiliary swtich	1	piece
2CCS500900R0161	ZLS931	Spare parts	1	piece
2CCA880212R0001	CMS-122PS	Sensor	1	piece
2CCA880102R0001	CMS-102PS	Sensor	1	piece

Categories

Low Voltage Products and Systems → Modular DIN Rail Products → Plug-in Distribution Systems → Plug-in Distribution Systems → Residual Current Circuit Breakers with Overcurrent Protection RCBO

