



## PRODUCT-DETAILS

**GAF1250-10-11-68****GAF1250-10-11 24-60V DC Contactor****General Information**

Extended Product Type	GAF1250-10-11-68
Product ID	1SFL647025R6811
EAN	7320500400807
Catalog Description	GAF1250-10-11 24-60V DC Contactor
Long Description	A 3-pole Contactor suitable for DC-1 applications where all three poles must be connected in series in a 1-pole configuration up to max 1000 VDC. Operated with wide control voltage range 24-60 V, DC

**Ordering**

Minimum Order Quantity	1 piece
Customs Tariff Number	85364900

**Popular Downloads**

Data Sheet, Technical Information	1SBC100214C0202
Instructions and	1SFC101045M9701

## Manuals

CAD Dimensional Drawing	2CDC001079B0201
-------------------------	-----------------

## Dimensions

Product Net Width	210 mm
Product Net Depth / Length	242 mm
Product Net Height	344 mm
Product Net Weight	15 kg

## Technical

Number of Main Contacts NO	1
Number of Main Contacts NC	0
Number of Auxiliary Contacts NO	1
Number of Auxiliary Contacts NC	1
Rated Operational Voltage	Main Circuit 1000 V
Conventional Free-air Thermal Current ( $I_{th}$ )	acc. to IEC 60947-4-1, Open Contactors $\theta = 40^\circ\text{C}$ 1260 A
Rated Operational Current DC-1 ( $I_e$ )	(1000 V) 3 Poles in Series, $40^\circ\text{C}$ 1250 A (1000 V) 3 Poles in Series, $55^\circ\text{C}$ 1040 A (1000 V) 3 Poles in Series, $70^\circ\text{C}$ 875 A (220 V) 3 Poles in Series, $40^\circ\text{C}$ 1250 A (220 V) 3 Poles in Series, $55^\circ\text{C}$ 1040 A (220 V) 3 Poles in Series, $70^\circ\text{C}$ 875 A (400 V) 3 Poles in Series, $40^\circ\text{C}$ 1250 A (400 V) 3 Poles in Series, $55^\circ\text{C}$ 1040 A (400 V) 3 Poles in Series, $70^\circ\text{C}$ 875 A (600 V) 3 Poles in Series, $40^\circ\text{C}$ 1250 A (600 V) 3 Poles in Series, $55^\circ\text{C}$ 1040 A (600 V) 3 Poles in Series, $70^\circ\text{C}$ 875 A
Rated Insulation Voltage ( $U_i$ )	acc. to UL/CSA 1000 V
Rated Impulse Withstand Voltage ( $U_{imp}$ )	Main Circuit 8 kV
Mechanical Durability	0.5 million
Maximum Mechanical Switching Frequency	300 cycles per hour
Coil Operating Limits	(acc. to IEC 60947-4-1) 0.85 x $U_c$ Min. ... 1.1 x $U_c$ Max. (at $\theta \leq 70^\circ\text{C}$ )
Rated Control Circuit Voltage ( $U_c$ )	DC Operation 24 ... 60 V
Coil Consumption	Holding at Max. Rated Control Circuit Voltage 50 Hz 12 V-A Holding at Max. Rated Control Circuit Voltage 60 Hz 12 V-A Holding at Max. Rated Control Circuit Voltage DC 4.5 W Pull-in at Max. Rated Control Circuit Voltage 50 Hz 850 V-A Pull-in at Max. Rated Control Circuit Voltage 60 Hz 850 V-A Pull-in at Max. Rated Control Circuit Voltage DC 950 V-A
Connecting Capacity Main Circuit	Bar 50 mm <sup>2</sup>
Connecting Capacity Auxiliary Circuit	Flexible with Ferrule 1x 0.75 ... 2.5 mm <sup>2</sup> Flexible with Insulated Ferrule 2x 0.75 ... 2.5 mm <sup>2</sup> Flexible 2x0.75 ... 2.5 mm <sup>2</sup> Solid 1 x 1 ... 4 mm <sup>2</sup>

Stranded 2 x 1 .... 4 mm<sup>2</sup>

Degree of Protection	acc. to IEC 60529, IEC 60947-1, EN 60529 Coil Terminals IP20 acc. to IEC 60529, IEC 60947-1, EN 60529 Main Terminals IP00
Terminal Type	Main Circuit: Bars

## Technical UL/CSA

Maximum Operating Voltage UL/CSA	Main Circuit 600 V
General Use Rating UL/CSA	(1000 V DC) 1210 A (440 V DC) 1210 A (600 V DC) 1210 A

## Environmental

Ambient Air Temperature	Operation -40 ... 70 °C Storage -40 ... +70 °C
Maximum Operating Altitude Permissible	Without Derating 3000 m
Resistance to Shock acc. to IEC 60068-2-27	Shock Direction: A 5 g Shock Direction: B1 5 g Shock Direction: B2 5 g Shock Direction: C1 5 g Shock Direction: C2 5 g

## Material Compliance

Conflict Minerals Reporting Template (CMRT)	9AKK108467A5658
REACH Declaration	2CMT2021-006202
RoHS Information	2CMT2021-006277
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
Toxic Substances Control Act - TSCA	2CMT2023-006525
WEEE B2C / B2B	Business To Business
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

## Certificates and Declarations

CB Certificate	SEMKO_SE-67143
CQC Certificate	CQC2012010304562753
Declaration of Conformity - CCC	2020980304001541
Declaration of Conformity - CE	2CMT003517
Declaration of Conformity - UKCA	2CMT2020-006118
EAC Certificate	9AKK107046A8618
UL Certificate	9AKK107046A9916
UL Listing Card	UL_E73397

## Container Information

Package Level 1 Units	box 1 piece
-----------------------	-------------

Package Level 1 Width	280 mm
Package Level 1 Depth / Length	375 mm
Package Level 1 Height	310 mm
Package Level 1 Gross Weight	16 kg
Package Level 1 EAN	7320500400807

---

## Classifications

---

Object Classification Code	Q
ETIM 7	EC002552 - Power contactor, DC switching
ETIM 8	EC002552 - Power contactor, DC switching
ETIM 9	EC002552 - Power contactor, DC switching
eClass	V11.0 : 27371018
UNSPSC	39121529
IDEA Granular Category Code (IGCC)	4763 >> Power contactor, DC switching

---

---

## Categories

---

Low Voltage Products and Systems → Control Products → Contactors → Block Contactors → GA Contactors → GAF1250

