

General Duty Safety Switches

Selection



3 SAFETY SWITCHES

System	Ampere Rating	Indoor — Type 1			Outdoor — Type 3R			Horsepower Ratings ^①					
		Catalog Number	List Price \$	Ship Wt.* Std. Pkg.	Catalog Number	List Price \$	Ship Wt.* Std. Pkg.	240V AC				250 Volt DC Std.	
								1-Phase, 2-Wire		2-Phase, 4-Wire			3-Phase, 3-Wire
Std.	Max.	Std.	Max.	Std.	Max.	Std.	Max.	Std.	Max.	Std.			

240 Volt Fusible

2-Pole, 2-Fuse, and Solid Neutral^{②③④}

240 Volt AC/250 Volt DC

	30	GF221N	127.00	35 ^⑤	GF221NR ^⑥	203.00	35 ^⑤	1½	3	—	—	3	7½	5
	60	GF222N	217.00	14	GF222NR	334.00	14	3	10	—	—	7½	15	10
	100	GF223N	437.00	23	GF223NR	492.00	24	7½	15	—	—	15	30	20
	200	GF224N	907.00	47	GF224NR	1287.00	48	15	—	—	—	25	60	40
	400	GF225NH ^⑦	2753.00	128	GF225NRH ^⑧	3730.00	130	15	—	—	—	50	125	50
	400	GF225N	2774.00	153	GF225NR	3752.00	157	15	—	—	—	50	125	50
	600	GF226NH ^⑦	5438.00	133	GF226NRH ^⑧	6897.00	135	15	—	—	—	75	200	—
	600	GF226N	5467.00	159	GF226NR	6929.00	159	15	—	—	—	75	200	—

3-Pole, 3-Fuse, and Solid Neutral^④

240 Volt AC/250 Volt DC

	30	GF321N	203.00	24 ^④	GF321NR ^⑥	302.00	24 ^④	1½	3	—	—	3	7½	5
	60	GF322N	334.00	15	GF322NR	454.00	15	3	10	—	—	7½	15	10
	100	GF323N	581.00	25	GF323NR	840.00	25	7½	15	—	—	15	30	20
	200	GF324N	1287.00	49	GF324NR	1524.00	50	15	—	—	—	25	60	40
	400	GF325NH ^⑦	3262.00	136	GF325NRH ^⑧	3934.00	138	15	—	—	—	50	125	50
	400	GF325N	3287.00	158	GF325NR	3955.00	162	15	—	—	—	50	125	50
	600	GF326NH ^⑦	6091.00	138	GF326NRH ^⑧	8171.00	141	15	—	—	—	75	200	—
	600	GF326N	6124.00	161	GF326NR	8205.00	165	15	—	—	—	75	200	—

240 Volt Non-Fusible^{③④}

2-Pole or 3-Pole

240 Volt AC/250 Volt DC

	30	GNF321	166.00	24 ^④	GNF321R ^⑥	302.00	24 ^④	—	3	—	—	7½	—	5
	60	GNF322	209.00	12	GNF322R	466.00	13	—	10	—	—	15	—	10
	100	GNF323	492.00	23	GNF323R	840.00	24	—	15	—	—	30	—	20
	200	GNF324	887.00	46	GNF324R	1505.00	47	—	15	—	—	60	—	40
	400	GNF325	2275.00	114	Use 600V Switch — HNF365R			—	15	—	—	125	—	50
	600	GNF326	4350.00	116	Use 600V Switch — HNF366R			—	15	—	—	200	—	—

* In pounds (lbs).

① Dual horsepower ratings: Std.- applies when non-time delay fuses are installed. Max.- applies when time-delay fuses are installed.

② These switches are UL-listed for application on grounded B-phase systems.

③ Suitable for use on 3-phase motor loads.

④ Service entrance labeled.

⑤ Has provision for ECHA type hub.

⑥ 5 switches per standard package.

⑦ 10 switches per standard package.

⑧ Height reduced switch (45.25 rather than 56 inches in height) for use with 500MCM or smaller conductors.