



#### Main

Range of product	GK3EF80
Product or component type	Auxiliary contact block
Pole contact composition	1 NO + 1 NC
Connections - terminals	Connector 1 cable 1...4 mm <sup>2</sup> - cable stiffness: solid Connector 1 cable 2.5 mm <sup>2</sup> - cable stiffness: flexible - without cable end Connector 1 cable 2.5 mm <sup>2</sup> - cable stiffness: flexible - with cable end Connector 2 cable 2.5 mm <sup>2</sup> - cable stiffness: flexible - with cable end
Quantity per set	Set of 10

#### Complementary

Mounting location	Right side
[Ui] rated insulation voltage	500 V - conforming to IEC 60947-1
[Ue] rated operational voltage	500 V
[Ith] conventional free air thermal current	6 A conforming to IEC 60947-5-1
Protection type	GB2CB... circuit breaker rating according to operational current for Ue ≤ 415 V for control circuit GG fuse ≤ 10 A for control circuit
Rated operational power in VA	360 VA at 48 V AC-15 - electrical durability: 20000 cycles 500 VA at 110...127 V AC-15 - electrical durability: 20000 cycles 800 VA at 220...240 V AC-15 - electrical durability: 20000 cycles 850 VA at 380...415 V AC-15 - electrical durability: 20000 cycles 700 VA at 440 V AC-15 - electrical durability: 20000 cycles 700 VA at 500 V AC-15 - electrical durability: 20000 cycles
Rated operational power in W	180 W at 24 V DC-13 - electrical durability: 1000 cycles 240 W at 48 V DC-13 - electrical durability: 1000 cycles 180 W at 60 V DC-13 - electrical durability: 1000 cycles 140 W at 110 V DC-13 - electrical durability: 1000 cycles 120 W at 220 V DC-13 - electrical durability: 1000 cycles
Tightening torque	0.8 N.m
Height	80 mm
Width	8.8 mm
Depth	105 mm
Product weight	0.031 kg