



Siemens Low Voltage Circuit Protection General Duty Safety Switches.  
 Type: Safety Switch, Enclosed General Duty Special Features: Non Fusible  
 Application: Construction, Industrial, Residential Std: UL98 V. Rating: 240V  
 A. Rating: 100A No. Of Poles: 3 Action: Single Throw Material: Galvanized  
 Steel Size: H 23.46 x W 11.67 x D 14.68 inches Enclosure: Type 3R  
 Mounting: 2 or 3 Point Mounting Lever O. Cycles: UL 98 Cycles  
 Environmental Conditions: Seismic T58569.01-1

fastening method	SURFACE
number of poles	3
suitability for operation	DISCONNECTING MEAN FOR SERVICE ENTRANCE / LOADS
<b>Electricity</b>	
ampacity	100 A
<b>Environmental conditions</b>	
ambient temperature during operation maximum	85 °C
ambient temperature during operation minimum	-29 °C
<b>Model</b>	
product brand name	SIEMENS
product sub brand name	VBII
product type designation	GENERAL DUTY SWITCH
type of electrical connection	MECHANICAL LUGS
<b>Mechanical Design</b>	
design of the housing	Type 3R
design of the actuating element	SINGLE THROW
material	STEEL
<b>General product approval</b>	
certificate of suitability	UL98

last modified:

9/15/2021 

