

External rotary handle, TeSys GS, black handle, front mounting, 2 positions I-O, NEMA 4-4X, for GS 30A Compact UL

GS2AH410

Main

Range of product	TeSys
Range	TeSys
Device short name	GS2AH
product or component type	Rotary handle
Range compatibility	TeSys TeSys GS GS1D fuse-switch disconnector
Type of operating handle	External frontal
handle colour	Black
Handle front plate colour	Grey

Complementary

Handle positions	O-I
Rotary handle padlocking	With
Switch rated current	30 A
Standards	UL CSA
net weight	0.4 lb(US) (0.2 kg)

Environment

NEMA degree of protection NEMA 4/4X

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	2.8 in (7.0 cm)
Package 1 Width	4.7 in (12.0 cm)
Package 1 Length	5.5 in (14.0 cm)
Package 1 Weight	7.8 oz (220.0 g)
Unit Type of Package 2	S03
Number of Units in Package 2	20
Package 2 Height	11.8 in (30.0 cm)
Package 2 Width	11.8 in (30.0 cm)
Package 2 Length	15.7 in (40.0 cm)

Package 2 Weight

10.787 lb(US) (4.893 kg)

Contractual warranty

Warranty

18 months

Sustainability

Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >

Well-being performance

Reach Free Of Svhc	
Toxic Heavy Metal Free	
Mercury Free	
Rohs Exemption Information	Yes
Reach Regulation	REACh Declaration
Eu Rohs Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
China Rohs Regulation	China RoHS declaration