# Product data sheet

Specifications





External rotary handle, TeSys GS, black handle, front mounting, 2 positions I-O, NEMA 4-4X, for GS 30-400A UL

GS2AH430

Product availability: Stock - Normally stocked in distribution facility

#### Price\*: 78.00 USD

#### Main

| TeSys<br>TeSys   |  |
|--|--|
| TeSys  |  |
|  |  |
| GS2AH  |  |
| Rotary handle  |  |
| TeSys TeSys GS GS2EU<br>TeSys TeSys GS GS2GU<br>TeSys TeSys GS GS2JU<br>TeSys TeSys GS GS2MU<br>TeSys TeSys GS GS2QU |  |
| External frontal   |  |
| Black  |  |
| Grey   |  |
|  |  |

### Complementary

| Handle positions         | 0-1                   |  |
|--------------------------|-----------------------|--|
| Rotary handle padlocking | With                  |  |
| Switch rated current     | 30 A                  |  |
|                          | 60 A                  |  |
|                          | 100 A                 |  |
|                          | 200 A                 |  |
|                          | 400 A                 |  |
| Standards                | CSA                   |  |
|                          | UL                    |  |
| Net Weight               | 0.53 lb(US) (0.24 kg) |  |

### Environment

NEMA Degree of Protection

NEMA 4/4X

### Ordering and shipping details

| Category          | US10I1122640  |
|-------------------|---------------|
| Discount Schedule | 0I11          |
| GTIN              | 3389119411875 |
| Returnability     | Yes           |
| Country of origin | FR            |

Price is "List Price" and may be subject to a trade discount - check with your local distributor or retailer for actual price.

## **Packing Units**

| <u>~</u>                     |                          |
|------------------------------|--------------------------|
| Unit Type of Package 1       | PCE                      |
| Number of Units in Package 1 | 1                        |
| Package 1 Height             | 2.0 in (5.0 cm)          |
| Package 1 Width              | 7.09 in (18.0 cm)        |
| Package 1 Length             | 7.09 in (18.0 cm)        |
| Package 1 Weight             | 8.8 oz (249.0 g)         |
| Unit Type of Package 2       | \$03                     |
| Number of Units in Package 2 | 20                       |
| Package 2 Height             | 11.8 in (30.0 cm)        |
| Package 2 Width              | 11.8 in (30.0 cm)        |
| Package 2 Length             | 15.7 in (40.0 cm)        |
| Package 2 Weight             | 12.033 lb(US) (5.458 kg) |

### **Contractual warranty**

Warranty

18 months

### Sustainability Screen Premium

**Green Premium<sup>TM</sup> label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >



Transparency RoHS/REACh

### Well-being performance

Reach Free Of Svhc
Toxic Heavy Metal Free
Mercury Free
Rohs Exemption Information Yes

#### **Certifications & Standards**

| Reach Regulation          | REACh Declaration  |
|---------------------------|--|
| Eu Rohs Directive         | Compliant<br>EU RoHS Declaration   |
| China Rohs Regulation     | China RoHS declaration   |
| Environmental Disclosure  | Product Environmental Profile  |
| Circularity Profile       | End of Life Information  |
| California Proposition 65 | WARNING: This product can expose you to chemicals including: Styrene, which is<br>known to the State of California to cause cancer. For more information go to<br>www.P65Warnings.ca.gov |