Product data sheet

Specifications





Switch disconnector fuse, TeSys GS, 3P, 30A, fuse type UL, size J

GS2EU3N

Product availability: Stock - Normally stocked in distribution facility

Price*: 260.00 USD

Main

| Range | TeSys | |
|--|--------------------------|--|
| Product Name | TeSys GS | |
| Device Short Name | GS2EU | |
| Product Or Component Type | Switch-disconnector-fuse | |
| Poles Description | 3P | |
| Protected Poles Description | 3t | |
| Contacts Type And Composition | 3 NO | |
| [Ith] Conventional Free Air Thermal Current | 30 A (at 104 °F (40 °C)) | |
| [le] Rated Operational Current | 30 A | |
| Fuse Type | UL | |
| Fuse Size | J | |
| Network Type | DC AC | |
| Network Frequency | 50/60 Hz | |

Complementary

| Type Of Operating Handle | External frontal | |
|---|---|--|
| Mounting Support | Rail | |
| | Plate | |
| [Ui] Rated Insulation Voltage | 750 V | |
| [Uimp] Rated Impulse Withstand Voltage | 8 kV | |
| Rated Operational Power In W | 15 kW 400 V | |
| | 18.5 kW 500 V | |
| | 25 kW 690 V | |
| Short-Circuit Withstand | 17.6 kA | |
| Mechanical Durability | 10000 cycles | |
| Electrical Durability | 6000 cycles | |
| Connections - Terminals | Power circuit lugs-ring terminals 0.000.02 in ² (213 mm ²) | |
| Tightening Torque | Power circuit 58.41 lbf.in (6.6 N.m) | |

Environment

Standards

UL98 CSA C22.2 No 4

Price is "List Price" and may be subject to a trade discount - check with your local distributor or retailer for actual price.

| Ip Degree Of Protection | IP20 IEC 60529 with terminal cover) | |
|--|-------------------------------------|--|
| Ambient Air Temperature For Operation | -4158 °F (-2070 °C) | |
| Ambient Air Temperature For Storage | -40176 °F (-4080 °C) | |
| Fire Resistance | 1760 °F (960 °C) body | |
| Height | 5.35 in (136 mm) | |
| Width | 5.88 in (149.3 mm) | |
| Depth | 4.84 in (123 mm) | |

Ordering and shipping details

| Category | US10I1122640 | |
|-------------------|---------------|--|
| Discount Schedule | 0111 | |
| Gtin | 3606480618529 | |
| Returnability | Yes | |
| Country Of Origin | TN | |

Packing Units

| Unit Type Of Package 1 | PCE |
|------------------------------|----------------------|
| Number Of Units In Package 1 | 1 |
| Package 1 Height | 6.38 in (16.2 cm) |
| Package 1 Width | 6.81 in (17.3 cm) |
| Package 1 Length | 7.09 in (18.0 cm) |
| Package 1 Weight | 4.63 lb(US) (2.1 kg) |

Sustainability Screen Premium

Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >



Transparency RoHS/REACh

Well-being performance

Reach Free Of Svhc
Toxic Heavy Metal Free
Mercury Free
Rohs Exemption Information Yes

Certifications & Standards

| Reach Regulation | REACh Declaration |
|---------------------------|--|
| Eu Rohs Directive | Compliant EU RoHS Declaration |
| China Rohs Regulation | China RoHS declaration |
| Environmental Disclosure | Product Environmental Profile |
| Circularity Profile | End of Life Information |
| California Proposition 65 | WARNING: This product can expose you to chemicals including: Styrene, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov |