Product data sheet





Switch disconnector fuse, TeSys GS, 3P, 200A, fuse type UL, size J

GS2MU3N

Product availability: Stock - Normally stocked in distribution

Price*: 1,181.00 USD

Main

Range	TeSys	
Product Name	TeSys GS	
Device Short Name	GS2MU	
Product Or Component Type	Switch-disconnector-fuse	
Device Application	Protection	
Poles Description	3P	
Protected Poles Description	cription 3t	
Contacts Type And Composition	3 NO	
[Ith] Conventional Free Air Thermal Current	200 A (at 104 °F (40 °C))	
[le] Rated Operational Current	Current 200 A	
Fuse Type	UL	
Fuse Size	J	
Network Type	DC AC	
Network Frequency 50/60 Hz		

Complementary

Type Of Operating Handle	External frontal	
Mounting Support	Plate	
[Ui] Rated Insulation Voltage	750 V	
[Uimp] Rated Impulse Withstand Voltage	8 kV	
Rated Operational Power In W	100 kW 400 V	
	140 kW 500 V	
	185 kW 690 V	
Breaking Capacity	1600 A 400 V	
Short-Circuit Withstand	t Withstand 200 kA	
Mechanical Durability	10000 cycles	
Electrical Durability	6000 cycles	
Connections - Terminals	Power circuit lugs-ring terminals 0.020.24 in² (16152 mm²)	
[Icm] Rated Short-Circuit Making Capacity	g 2 kA 400 V	
Tightening Torque	Power circuit 75.23 lbf.in (8.5 N.m)	

Price is "List Price" and may be subject to a trade discount - check with your local distributor or retailer for actual price.

Environment

Standards	UL98 CSA C22.2 No 4	
Ip Degree Of Protection	IP20 IEC 60529 with terminal cover)	
Ambient Air Temperature For Operation	-4158 °F (-2070 °C)	
Ambient Air Temperature For Storage	-40176 °F (-4080 °C)	
Fire Resistance	1760 °F (960 °C) body	
Height	7.68 in (195 mm)	
Width	7.72 in (196.2 mm)	
Depth	5.12 in (130 mm)	

Ordering and shipping details

Category	US10I1122640	
Discount Schedule	0111	
Gtin	3606480512360	
Returnability	Yes	
Country Of Origin	FR	

Packing Units

Unit Type Of Package 1	PCE	
Number Of Units In Package 1	1	
Package 1 Height	5.71 in (14.500 cm)	
Package 1 Width	9.65 in (24.500 cm)	
Package 1 Length	12.60 in (32.000 cm)	
Package 1 Weight 7.78 lb(US) (3.530 kg)		
Unit Type Of Package 2	2 S04	
Number Of Units In Package 2	skage 2 3	
Package 2 Height	11.81 in (30.000 cm)	
Package 2 Width	15.75 in (40.000 cm)	
Package 2 Length 23.62 in (60.000 cm)		
Package 2 Weight	24.85 lb(US) (11.270 kg)	
Unit Type Of Package 3	pe Of Package 3 P06	
Number Of Units In Package 3	e 3 12	
Package 3 Height	29.53 in (75.000 cm)	
Package 3 Width	23.62 in (60.000 cm)	
Package 3 Length	31.50 in (80.000 cm)	
Package 3 Weight 122.00 lb(US) (55.336 kg)		



Green PremiumTM **label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

Well-being performance

Ø	Reach Free Of Svhc	
⊘	Toxic Heavy Metal Free	
Ø	Mercury Free	
⊘	Rohs Exemption Information	Yes

Certifications & Standards

California Proposition 65	WARNING: This product can expose you to chemicals including: Styrene, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov
Circularity Profile	End of Life Information
Environmental Disclosure	Product Environmental Profile
China Rohs Regulation	China RoHS declaration
Eu Rohs Directive	Compliant EU RoHS Declaration
Reach Regulation	REACh Declaration