Product data sheet

Specifications





Switch disconnector fuse, TeSys GS, 3P, 400A, fuse type UL, size J

GS2QU3N

Product availability: Stock - Normally stocked in distribution facility

Price*: 2,252.00 USD

Main

Range	TeSys	
Product Name	TeSys GS	
Device Short Name	GS2QU	
Product Or Component Type	Switch-disconnector-fuse	
Device Application	Protection	
Poles Description	3P	
Protected Poles Description	3t	
Contacts Type And Composition	3 NO	
[Ith] Conventional Free Air Thermal Current	400 A (at 104 °F (40 °C))	
[Ie] Rated Operational Current	400 A	
Fuse Type	UL	
Fuse Size	J	
Network Type	AC DC	
Network Frequency	50/60 Hz	

Complementary

· · · · · · · · · · · · · · · · · · ·		
Type Of Operating Handle	External frontal	
Mounting Support	Plate	
[Ui] Rated Insulation Voltage	800 V	
[Uimp] Rated Impulse Withstand Voltage	8 KV	
Rated Operational Power In W	220 kW 690 V 220 kW 500 V 220 kW 400 V	
Short-Circuit Withstand	200 kA	
Mechanical Durability	10000 cycles	
Electrical Durability	6000 cycles	
Connections - Terminals	Power circuit lugs-ring terminals 0.020.47 in ² (13.3304 mm ²)	
Tightening Torque	Power circuit 500.07 lbf.in (56.5 N.m)	

Environment

Standards

CSA C22.2 No 4 UL98

Price is "List Price" and may be subject to a trade discount - check with your local distributor or retailer for actual price.

Ip Degree Of Protection	IP20 IEC 60529 with terminal cover)	
Ambient Air Temperature For Operation	-4158 °F (-2070 °C)	
Ambient Air Temperature For Storage	-40176 °F (-4080 °C)	
Height	9.45 in (240 mm)	
Width	10.20 in (259 mm)	
Depth	7.09 in (180 mm)	

Ordering and shipping details

Category	US10I1122640	
Discount Schedule	0111	
Gtin	3606480512384	
Returnability	Yes	
Country Of Origin	US	

Packing Units

Unit Type Of Package 1	PCE	
Number Of Units In Package 1	1	
Package 1 Height	11.42 in (29.000 cm)	
Package 1 Width	21.26 in (54.000 cm)	
Package 1 Length	16.54 in (42.000 cm)	
Package 1 Weight	15.13 lb(US) (6.864 kg)	
Unit Type Of Package 2	P12	
Number Of Units In Package 2	4	
Package 2 Height	29.53 in (75.000 cm)	
Package 2 Width	31.50 in (80.000 cm)	
Package 2 Length	47.24 in (120.000 cm)	
Package 2 Weight	86.99 lb(US) (39.456 kg)	

Sustainability Screen Premium

Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >



Transparency RoHS/REACh

Well-being performance

Reach Free Of Svhc
Toxic Heavy Metal Free
Mercury Free
Rohs Exemption Information Yes

Certifications & Standards

Reach Regulation	REACh Declaration
Eu Rohs Directive	Compliant EU RoHS Declaration
China Rohs Regulation	China RoHS declaration
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information
California Proposition 65	WARNING: This product can expose you to chemicals including: Styrene, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov