Specifications

Green



() Discontinued

Direct rotary handle, TeSys GV7, red, padlockable, IP40

GV7AB11

() Discontinued on: May 17, 2022

Product availability: Non-Stock - Not normally stocked in distribution facility

Main

Range	TeSys	
Device short name	GV7AB	
Product or Component Type	Auxiliary contact block	
Device Application	Signalling	
Range compatibility	TeSys TeSys GV5 motor circuit breaker TeSys TeSys GV6 motor circuit breaker TeSys TeSys GV7 motor circuit breaker	
Auxiliary contact composition	1 C/O	
Auxiliary contacts type	Low level contacts	
Auxiliary contacts operation	Instantaneous	
[Ith] conventional free air thermal current	tional free air thermal 6 A IEC 60947-5-1	
[Ue] rated operational voltage	<= 690 V AC 50/60 Hz <= 110 V DC	
[le] rated operational current	5 A AC-12 Ue: <= 690 V IEC 60947-5-1 5 A AC-15 Ue: <= 48 V IEC 60947-5-1 4 A AC-15 Ue: 110127 V IEC 60947-5-1 3 A AC-15 Ue: 230240 V IEC 60947-5-1 2.5 A AC-15 Ue: 380440 V IEC 60947-5-1 0.1 A AC-15 Ue: 660690 V IEC 60947-5-1 2 A DC-12 Ue: <= 48 V IEC 60947-5-1 0.5 A DC-12 Ue: 110 V IEC 60947-5-1 0.5 A DC-14 Ue: <= 24 V IEC 60947-5-1 0.25 A DC-14 Ue: <= 24 V IEC 60947-5-1 0.25 A DC-14 Ue: 48 V IEC 60947-5-1 0.1 A DC-14 Ue: 110 V IEC 60947-5-1	
Minimum switching current	5 mA	
Minimum switching voltage	12 V	

Complementary

[Ui] rated insulation voltage	690 V IEC 60947-1	
Protection type	GG fuse 10 A maximum GB2CB circuit breaker 10 A maximum	
Mechanical durability	50000 cycles	
mounting location	Inside the circuit breaker	
Connections - terminals	screw clamps terminals 1 0.002 in ² (1.5 mm ²)flexible with cable end screw clamps terminals 1 0.002 in ² (1.5 mm ²)flexible without cable end screw clamps terminals 1 0.002 in ² (1.5 mm ²)rigid	
Net Weight	0.033 lb(US) (0.015 kg)	

Price is "List Price" and may be subject to a trade discount - check with your local distributor or retailer for actual price.

Ordering and shipping details

Category	US10I1122366	
Discount Schedule	0I11	
GTIN	3389110617481	
Returnability	No	
Country of origin	FR	

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1

Contractual warranty

Warranty

18 months

Sustainability Screen

Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >



Transparency RoHS/REACh

Well-being performance

Reach Free Of Svhc

Toxic Heavy Metal Free	
Mercury Free	
Rohs Exemption Information	Yes

Certifications & Standards

Eu Rohs Directive	Compliant
	EU RoHS Declaration
China Rohs Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
Environmental Disclosure	Product Environmental Profile
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.
Circularity Profile	No need of specific recycling operations
California Proposition 65	WARNING: This product can expose you to chemicals including: Antimony oxide & Antimony trioxide, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov

Connections and Schema

GV7 AE11, GV7 AB11

Add-on auxiliary contacts according to their location

Location 1 C/O contact Location 2 Trip indication Location 3 Electrical fault indication Location 4 C/O contact

