Specifications



() Discontinued

# Voltage release, TeSys GV7, MX shunt trip, 110 to 130VAC50/60Hz

GV7AS107

Discontinued on: May 17, 2022

## Product availability: Non-Stock - Not normally stocked in distribution facility

#### Main

| Range                     | TeSys   |
|---------------------------|---|
| Product or Component Type | Shunt trip  |
| Device short name         | GV7AS   |
| Device Application        | Control   |
| Range compatibility       | TeSys TeSys GV5<br>TeSys TeSys GV6<br>TeSys TeSys GV7 |

### Complementary

| [Uc] control circuit voltage    | 110130 V AC 50/60 Hz   |
|---------------------------------|--|
| Control circuit voltage limits  | 0.71.1 Un  |
| [Ui] rated insulation voltage   | 690 V AC IEC 60947-1<br>600 V AC UL 508<br>600 V AC CSA C22.2 No 14  |
| Threshold tripping voltage      | 0.20.75 Ue   |
| Inrush power in VA              | 10 VA AC   |
| Hold-in Power Consumption in VA | 5 VA AC  |
| Operating time                  | < 50 ms IEC 60947-1  |
| On-load factor                  | 100 %  |
| Connections - terminals         | screw clamp terminals 1 0.002 in <sup>2</sup> (1 mm <sup>2</sup> )flexible with cable end<br>screw clamp terminals 1 0.002 in <sup>2</sup> (1.5 mm <sup>2</sup> )flexible without cable end<br>screw clamp terminals 1 0.002 in <sup>2</sup> (1.5 mm <sup>2</sup> )solid |
| Tightening torque               | 1.2 N.m screw clamp terminals  |
| Net Weight                      | 0.231 lb(US) (0.105 kg)  |
| Quantity per Set                | Set of 10  |

#### Ordering and shipping details

| Category          | US10I1122366  |  |
|-------------------|---------------|--|
| Discount Schedule | 0111          |  |
| GTIN              | 3389110566949 |  |
| Returnability     | No            |  |
| Country of origin | FR            |  |

#### **Packing Units**

Price is "List Price" and may be subject to a trade discount - check with your local distributor or retailer for actual price.

| Unit Type of Package 1       | PCE             |
|------------------------------|-----------------|
| Number of Units in Package 1 | 1               |
| Package 1 Height             | 1.6 in (4 cm)   |
| Package 1 Width              | 3.3 in (8.3 cm) |
| Package 1 Length             | 2.5 in (6.3 cm) |
| Package 1 Weight             | 4.2 oz (120 g)  |

#### **Contractual warranty**

Warranty

18 months

#### **Sustainability**

**Green Premium<sup>™</sup> label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >

#### Well-being performance

| Reach Free Of Svhc         |   |
|----------------------------|---|
| Toxic Heavy Metal Free     |   |
| Mercury Free               |   |
| Rohs Exemption Information | Yes   |
| Eu Rohs Directive          | Compliant<br>EU RoHS Declaration  |
| China Rohs Regulation      | China RoHS declaration<br>Pro-active China RoHS declaration (out of China RoHS legal scope)   |
| Weee                       | The product must be disposed on European Union markets following specific waste<br>collection and never end up in rubbish bins.   |
| California Proposition 65  | WARNING: This product can expose you to chemicals including: Antimony oxide & Antimony trioxide, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov |