# **Product data sheet**

Specification





## TeSys Deca - auxiliary contact - 1 NC + 1 NC (fault)

GVAD0101

Product availability: Stock - Normally stocked in distribution facility

Price\*: 54.00 USD

### Main

Range	TeSys	
	TeSys Deca	
Device Short Name	GVAD	
Product Or Component Type	Auxiliary contact block	
Product Compatibility	GV3L	
	GV2P	
	GV2LE	
	GV2RT	
	GV2L	
	GV2ME	
	GV3P	
Mounting Location	Left side	
Auxiliary Contacts Operation	Fault signal 1 NC	
Pole Contact Composition	2 NC	

#### Complementary

Complementary	
[Ui] Rated Insulation Voltage	690 V IEC 60947-1 300 V UL 508 300 V CSA C22.2 No 14
[Ue] Rated Operational Voltage	48690 V AC 24240 V DC
[Ith] Conventional Free Air Thermal Current	6 A 2.5 A for fault signalling
Mechanical Durability	100000 cycles
Minimum Switching Current	5 mA
Minimum Switching Voltage	17 V
Protection Type	GB2CB circuit breaker GG fuse 10 A
Rated Operational Power In Va	300 VA 48 V AC-15 100000 cycles 414 VA 690 V AC-15 100000 cycles 500 VA 110127 V AC-15 100000 cycles 500 VA 500 V AC-15 100000 cycles 650 VA 440 V AC-15 100000 cycles 720 VA 230240 V AC-15 100000 cycles 850 VA 380415 V AC-15 100000 cycles 36 VA 24 V AC-14 1000 cycles 48 VA 48 V AC-14 1000 cycles 72 VA 110127 V AC-14 1000 cycles

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Rated Operational Power In W	120 W 240 V DC-13 100000 cycles 140 W 110 V DC-13 100000 cycles 140 W 24 V DC-13 100000 cycles 180 W 60 V DC-13 100000 cycles 240 W 48 V DC-13 100000 cycles	
	15 W 48 V DC-13 1000 cycles 24 W 24 V DC-13 1000 cycles 9 W 60 V DC-13 1000 cycles	
Tightening Torque	12.39 lbf.in (1.4 N.m) screw clamp terminals	
Height	3.50 in (89 mm)	
Width	0.37 in (9.3 mm)	
Depth	2.60 in (66 mm)	
Net Weight	0.12 lb(US) (0.055 kg)	
Color	Dark grey	

### **Environment**

<b>Environmental Characteristic</b>	Normal environment	
Product Certifications	UKCA	

# Ordering and shipping details

Category	US10I1122367	
Discount Schedule	0111	
Gtin	3389110343526	
Returnability	Yes	
Country Of Origin	US	

## **Packing Units**

Unit Type Of Package 1	PCE	
Number Of Units In Package 1	1	
Package 1 Height	0.59 in (1.500 cm)	
Package 1 Width	2.76 in (7.000 cm)	
Package 1 Length	3.54 in (9.000 cm)	
Package 1 Weight	1.52 oz (43.000 g)	
Unit Type Of Package 2	BB1	
Number Of Units In Package 2	10	
Package 2 Height	3.74 in (9.500 cm)	
Package 2 Width	3.86 in (9.800 cm)	
Package 2 Length	5.91 in (15.000 cm)	
Package 2 Weight	16.61 oz (471.000 g)	
Unit Type Of Package 3	S02	
Number Of Units In Package 3	60	
Package 3 Height	5.91 in (15.000 cm)	
Package 3 Width	11.81 in (30.000 cm)	
Package 3 Length	15.75 in (40.000 cm)	
Package 3 Weight	6.92 lb(US) (3.138 kg)	

## **Contractual warranty**

Warranty

Jun 6, 2024

18 months

### Sustainability Green Premium

**Green Premium<sup>TM</sup> label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

### Well-being performance

<b>⊘</b>	Reach Free Of Svhc	
<b>⊘</b>	Toxic Heavy Metal Free	
<b>⊘</b>	Mercury Free	
<b>⊘</b>	Rohs Exemption Information	Yes

#### **Certifications & Standards**

Declaration
Declaration
HS declaration
China RoHS declaration (out of China RoHS legal scope)
Environmental Profile
ct must be disposed on European Union markets following specific waste and never end up in rubbish bins.
fe Information
6: This product can expose you to chemicals including: Antimony oxide & trioxide, which is known to the State of California to cause cancer. For mation go to www.P65Warnings.ca.gov

### Connections and Schema

GVAD0101