

Product data sheet

Specifications



TeSys Deca - auxiliary contact - 1 NC + 1 NO (fault)

GVAD1001

Product availability: Stock - Normally stocked in distribution facility

Price*: 54.00 USD

Main

Range	TeSys TeSys Deca
Device Short Name	GVAD
Product Or Component Type	Auxiliary contact block
Product Compatibility	GV2P GV2LE GV3L GV2ME GV2RT GV3P GV2L
Mounting Location	Left side
Auxiliary Contacts Operation	Fault signal 1 NO
Pole Contact Composition	1 NO + 1 NC

Complementary

[Ui] Rated Insulation Voltage	690 V IEC 60947-1 300 V UL 508 300 V CSA C22.2 No 14
[Ue] Rated Operational Voltage	48...690 V AC 24...240 V DC
[Ith] Conventional Free Air Thermal Current	6 A 2.5 A for fault signalling
Mechanical Durability	100000 cycles
Minimum Switching Current	5 mA
Minimum Switching Voltage	17 V
Protection Type	GB2CB... circuit breaker GG fuse 10 A
Rated Operational Power In Va	300 VA 48 V AC-15 100000 cycles 414 VA 690 V AC-15 100000 cycles 500 VA 110...127 V AC-15 100000 cycles 500 VA 500 V AC-15 100000 cycles 650 VA 440 V AC-15 100000 cycles 720 VA 230...240 V AC-15 100000 cycles 850 VA 380...415 V AC-15 100000 cycles 36 VA 24 V AC-14 1000 cycles 48 VA 48 V AC-14 1000 cycles 72 VA 110...127 V AC-14 1000 cycles

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Rated Operational Power In W	120 W 240 V DC-13 100000 cycles
	140 W 110 V DC-13 100000 cycles
	140 W 24 V DC-13 100000 cycles
	180 W 60 V DC-13 100000 cycles
	240 W 48 V DC-13 100000 cycles
	15 W 48 V DC-13 1000 cycles
	24 W 24 V DC-13 1000 cycles
	9 W 60 V DC-13 1000 cycles
Tightening Torque	12.39 lbf.in (1.4 N.m) screw clamp terminals
Height	3.50 in (89 mm)
Width	0.37 in (9.3 mm)
Depth	2.60 in (66 mm)
Net Weight	0.12 lb(US) (0.055 kg)
Color	Dark grey

Environment

Environmental Characteristic	Normal environment
Product Certifications	UKCA

Ordering and shipping details

Category	US10I1122367
Discount Schedule	0I11
Gtin	3389110343540
Returnability	Yes
Country Of Origin	US

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	0.59 in (1.500 cm)
Package 1 Width	2.56 in (6.500 cm)
Package 1 Length	3.54 in (9.000 cm)
Package 1 Weight	1.64 oz (46.500 g)
Unit Type Of Package 2	BB1
Number Of Units In Package 2	10
Package 2 Height	3.74 in (9.500 cm)
Package 2 Width	3.74 in (9.500 cm)
Package 2 Length	5.91 in (15.000 cm)
Package 2 Weight	18.20 oz (516.000 g)
Unit Type Of Package 3	S02
Number Of Units In Package 3	60
Package 3 Height	5.91 in (15.000 cm)
Package 3 Width	11.81 in (30.000 cm)
Package 3 Length	15.75 in (40.000 cm)
Package 3 Weight	7.38 lb(US) (3.347 kg)

Contractual warranty

Warranty	18 months
----------	-----------

Sustainability

Green Premium™ label is Schneider Electric’s commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product’s sustainability >](#)



Transparency RoHS/REACH

Well-being performance

✓	Reach Free Of Svhc	
✓	Toxic Heavy Metal Free	
✓	Mercury Free	
✓	Rohs Exemption Information	Yes

Certifications & Standards

Reach Regulation	REACH Declaration
Eu Rohs Directive	Compliant EU RoHS Declaration
China Rohs Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
Environmental Disclosure	Product Environmental Profile
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.
Circularity Profile	End of Life Information
California Proposition 65	WARNING: This product can expose you to chemicals including: Antimony oxide & Antimony trioxide, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov

Connections and Schema

GVAD1001

