Product data sheet

Specification





TeSys Deca - auxiliary contact block - 2 NO

GVAED101

Product availability: Non-Stock - Not normally stocked in distribution facility

Price*: 54.00 USD

Main

Range	TeSys TeSys Deca	
Device Short Name	GVAED	
Product Or Component Type	Auxiliary contact block	
Product Compatibility	GV3P GV3L	
Mounting Location	Front side	
Auxiliary Contacts Operation	Fault signal 1 NO	
Pole Contact Composition	2 NO	
Quantity Per Set	Set of 1	

Complementary

Complementary		
[Ui] Rated Insulation Voltage	600 V UL 508 690 V IEC 60947-1 600 V CSA C22.2 No 14	
[Ue] Rated Operational Voltage	24240 V AC 2460 V DC	
[Ith] Conventional Free Air Thermal Current	2.5 A	
Mechanical Durability	100000 cycles	
Minimum Switching Current	5 mA	
Minimum Switching Voltage	17 V	
Protection Type	GB2CB circuit breaker GG fuse 10 A	
Rated Operational Power In Va	300 VA 48 V AC-15 100000 cycles 400 VA 690 V AC-15 100000 cycles 500 VA 110127 V AC-15 100000 cycles 500 VA 500 V AC-15 100000 cycles 650 VA 440 V AC-15 100000 cycles 720 VA 230240 V AC-15 100000 cycles 850 VA 380415 V AC-15 100000 cycles	
Rated Operational Power In W	120 W 240 V DC-13 100000 cycles 140 W 110 V DC-13 100000 cycles 140 W 24 V DC-13 100000 cycles 180 W 60 V DC-13 100000 cycles 240 W 48 V DC-13 100000 cycles	
Tightening Torque	12.39 lbf.in (1.4 N.m) screw clamp terminals	
Height	0.43 in (11 mm)	
Width	1.77 in (45 mm)	

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Depth	1.14 in (29 mm)
Net Weight	0.11 lb(US) (0.05 kg)

Environment

Environmental Characteristic	Normal environment	
Product Certifications	UKCA	

Ordering and shipping details

Category	US10l1122367	
Discount Schedule	0111	
Gtin	3389119405478	
Returnability	No	
Country Of Origin	US	

Packing Units

_		
Unit Type Of Package 1	PCE	
Number Of Units In Package 1	1	
Package 1 Height	0.47 in (1.2 cm)	
Package 1 Width	1.97 in (5.0 cm)	
Package 1 Length	2.36 in (6.0 cm)	
Package 1 Weight	0.63 oz (18.0 g)	
Unit Type Of Package 2	BB1	
Number Of Units In Package 2	10	
Package 2 Height	1.18 in (3.0 cm)	
Package 2 Width	5.91 in (15.0 cm)	
Package 2 Length	6.30 in (16.0 cm)	
Package 2 Weight	6.56 oz (186.0 g)	
Unit Type Of Package 3	S02	
Number Of Units In Package 3	220	
Package 3 Height	5.91 in (15.0 cm)	
Package 3 Width	11.81 in (30.0 cm)	
Package 3 Length	15.75 in (40.0 cm)	
Package 3 Weight	9.69 lb(US) (4.395 kg)	

Contractual warranty

Warranty 18 months



Green PremiumTM **label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

Well-being performance

⊘	Reach Free Of Svhc	
⊘	Toxic Heavy Metal Free	
⊘	Mercury Free	
⊘	Rohs Exemption Information	Yes

Certifications & Standards

Reach Regulation	REACh Declaration
Eu Rohs Directive	Compliant EU RoHS Declaration
China Rohs Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
Environmental Disclosure	Product Environmental Profile
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.
Circularity Profile	End of Life Information
California Proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov

Connections and Schema

GVAED101

