



# TeSys GV2 & GV3 - auxiliary contact block - 1 NO + 1 NC

GVAN113

#### Main

Range	TeSys
	TeSys Deca
Device short name	GVAN
product or component type	Auxiliary contact block
Product compatibility	GV3P
	GV2RT
	GV2P
	GV3L
	GV2ME
	GV2L
	GV2LE
mounting location	Left side
Pole contact composition	1 NO + 1 NC

## Complementary

Complementary		
[Ui] rated insulation voltage	600 V conforming to UL 508 690 V conforming to IEC 60947-1 600 V conforming to CSA C22.2 No 14	
[Ue] rated operational voltage	48690 V AC 24240 V DC	
[Ith] conventional free air thermal current	6 A	
Minimum switching current	5 mA	
Minimum switching voltage	17 V	
Protection type	GB2CB circuit breaker GG fuse 10 A	
Rated operational power in VA	300 VA at 48 V AC-15 - electrical durability: 100000 cycles 414 VA at 690 V AC-15 - electrical durability: 100000 cycles 500 VA at 110127 V AC-15 - electrical durability: 100000 cycles 500 VA at 500 V AC-15 - electrical durability: 100000 cycles 650 VA at 440 V AC-15 - electrical durability: 100000 cycles 720 VA at 230240 V AC-15 - electrical durability: 100000 cycles 850 VA at 380415 V AC-15 - electrical durability: 100000 cycles	
Rated operational power in W	120 W at 240 V DC-13 - electrical durability: 100000 cycles 140 W at 110 V DC-13 - electrical durability: 100000 cycles 140 W at 24 V DC-13 - electrical durability: 100000 cycles 180 W at 60 V DC-13 - electrical durability: 100000 cycles 240 W at 48 V DC-13 - electrical durability: 100000 cycles	
Height	89 mm	
Width	9.3 mm	
Depth	66 mm	
Colour	Dark grey	

### **Environment**

Environmental characteristic	Normal environment	
Product certifications	UKCA	

## **Packing Units**

racking office	
Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	1.0 cm
Package 1 Width	6.5 cm
Package 1 Length	9.0 cm
Package 1 Weight	25.0 g
Unit Type of Package 2	BB1
Number of Units in Package 2	10
Package 2 Height	9.8 cm
Package 2 Width	10.0 cm
Package 2 Length	15.3 cm
Package 2 Weight	500.0 g
Unit Type of Package 3	S02
Number of Units in Package 3	60
Package 3 Height	15.0 cm
Package 3 Width	30.0 cm
Package 3 Length	40.0 cm
Package 3 Weight	3.325 kg

## **Contractual warranty**

Warranty 18 months



**Green Premium**<sup>TM</sup> **label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

#### Well-being performance

<b>Ø</b>	Reach Free Of Svhc	
<b>⊘</b>	Toxic Heavy Metal Free	
<b>Ø</b>	Mercury Free	
<b>⊘</b>	Rohs Exemption Information	Yes

#### **Certifications & Standards**

Reach Regulation	REACh Declaration
Eu Rohs Directive	Compliant EU RoHS Declaration
China Rohs Regulation	China RoHS declaration  Pro-active China RoHS declaration (out of China RoHS legal scope)
Environmental Disclosure	Product Environmental Profile
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Circularity Profile	End of Life Information