



# Undervoltage release (MN), TeSys Deca, 200V AC 50 Hz

GVAU207

Product availability: Stock - Normally stocked in distribution facility

Price\*: 81.00 USD

#### Main

Range	TeSys TeSys Deca
Product or Component Type	Undervoltage release
Device short name	GVAU

## Complementary

· · · · · · · · · · · · · · · · · ·	
Range compatibility	TeSys GV2ME
	TeSys GV2LE
	TeSys GV2L
	TeSys GV2P
	TeSys GV3L
	TeSys GV3P
	TeSys Deca
[Uc] control circuit voltage	200 V AC 50 Hz
	200220 V AC 60 Hz
Control circuit voltage limits	0.851.1 Un
[Ui] rated insulation voltage	690 V AC IEC 60947-1
	600 V AC UL 60947-4-1
	600 V AC CSA C22.2 No 60947-4-1
Threshold tripping voltage	0.70.35 Un
Inrush power in VA	12 VA AC
Inrush power in W	8 W
Hold-in Power Consumption in VA	3.5 VA AC
Hold-in power consumption in W	1.1 W
Operating time	1015 ms IEC 60947-1
On-load factor	100 %
Connections - terminals	screw clamp terminals 1 0.0020.004 in² (12.5 mm²)solid
	screw clamp terminals 2 0.0020.004 in² (12.5 mm²)solid
	screw clamp terminals 1 0.0010.004 in <sup>2</sup> (0.752.5 mm <sup>2</sup> )flexible without cable end
	screw clamp terminals 2 0.0010.004 in <sup>2</sup> (0.752.5 mm <sup>2</sup> )flexible without cable end
	screw clamp terminals 1 0.0010.002 in <sup>2</sup> (0.751.5 mm <sup>2</sup> )flexible with cable end
	screw clamp terminals 2 0.0010.002 in² (0.751.5 mm²)flexible with cable end
Tightening torque	< 1.4 N.m screw clamp terminals
Mechanical durability	10000 cycles with GV3P and GV3L
·	30000 cycles with GV2ME and GV2P
Quantity per Set	Set of 10
Height	3.5 in (89 mm)
Width	0.7 in (18 mm)
Depth	2.6 in (66 mm)

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Net Weight	0.231 lb(US) (0.105 kg)
color	Dark grey

## Ordering and shipping details

Category	US10I1122367	
Discount Schedule	0111	
GTIN	3389110345988	
Returnability	Yes	
Country of origin	US	

## **Packing Units**

Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Height	3.3 in (8.3 cm)	
Package 1 Width	1.4 in (3.6 cm)	
Package 1 Length	3.6 in (9.1 cm)	
Package 1 Weight	4.09 oz (116.0 g)	

## **Contractual warranty**

Warranty 18 months



**Green Premium<sup>TM</sup> label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

## Well-being performance

<b>②</b>	Reach Free Of Svhc	
<b>Ø</b>	Toxic Heavy Metal Free	
<b>Ø</b>	Mercury Free	
	Rohs Exemption Information	Yes

#### **Certifications & Standards**

Reach Regulation	REACh Declaration
Eu Rohs Directive	Compliant
	EU RoHS Declaration
China Rohs Regulation	China RoHS declaration
	Pro-active China RoHS declaration (out of China RoHS legal scope)
<b>Environmental Disclosure</b>	Product Environmental Profile
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.
Circularity Profile	End of Life Information
California Proposition 65	WARNING: This product can expose you to chemicals including: Antimony oxide & Antimony trioxide, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov

## Connections and Schema

GVAU•••

