

PRODUCT-DETAILS

## **HKF1-01** HKF1-01 Aux.-contact for front mounting



General Information		
Extended Product Type	HKF1-01	
Product ID	1SAM201901R1004	
EAN	4013614502644	
Catalog Description	HKF1-01 Auxcontact for front mounting	
Long Description	Auxiliary contacts HKF1 with screw terminals change position with the main contacts of the manual motor starter. They are mounted on the front side of manual motor starters MS116, MS132 or MS165. Auxiliary contacts HKF1 are available as normally open or normally closed contacts.	
Ordering		
Minimum Order Quantity	10 piece	
Customs Tariff Number	85365080	
Popular Downloads		
Data Sheet, Technical Information	1SBC100214C0202	
© 2024 ABB. All rights reserved	. 2024/11/15 Subject to change	without notice

Instructions and	2CDC131011M6802
Manuals	2CDC131034M6801 2CDC131022M6802
	2CDC131120M6801
	2CDC131081M6801
	2CDC131082M6801
Instructions and	1SBC100214C0202
Manuals (Part 3) CAD Dimensional	2CDC001079B0201
Drawing	
Dimensions	
Product Net Width	45 mm
Product Net Height	12.5 mm
Product Net Depth / Length	26.5 mm
Product Net Weight	0.013 kg
Technical	
Terminal Type	Screw Terminals
Rated Operational	250 V
Voltage	
Rated Operational	(24 V) 3 A
Current AC-15 (l <sub>e</sub> )	(120 V) 3 A
	(240 V) 1.5 A
Rated Operational	(24 V) 1 A
Current DC-13 (l <sub>e</sub> )	(125 V) 0.27 A (250 V) 0.11 A
Rated Frequency (f)	Auxiliary Circuit DC
Rated Frequency (1)	Auxiliary Circuit 50 Hz
	Auxiliary Circuit 60 Hz
Rated Impulse	Auxiliary Circuit 6 kV
Withstand Voltage (U <sub>imp</sub>	
) Rated Insulation Voltage	250 V
(U <sub>i</sub> )	
Degree of Protection	IP20
Electrical Durability	100000 cycle
Mechanical Durability	100000 cycle
Connecting Capacity	Flexible with Ferrule 1/2x 0.75 1.5 mm <sup>2</sup>
Auxiliary Circuit	Flexible with Insulated Ferrule 1/2x 0.75 1.5 mm <sup>2</sup>
	Flexible 1/2x 0.75 1.5 mm² Rigid 1/2x 1.0 2.5 mm²
Tightening Torque	Auxiliary Circuit 0.8 1.2 N·m
Wire Stripping Length	Auxiliary Circuit 8 mm
Recommended Screw Driver	M3 Pozidriv 2
Number of Auxiliary	0
Contacts NO	
Number of Auxiliary Contacts NC	1
Product Name	Auxiliary Contact
Suitable For	MS116
	MS132
	M0132 MS165
	M0165
Suitable for Product	5:Manual Motor Starters

© 2024 ABB. All rights reserved.

Subject to change without notice

Class	Manual Motor Starters
Accessory Group	Electrical
Accessory Type	Auxiliary Contact

Technical UL/CSA	
Maximum Operating Voltage UL/CSA	Main Circuit 250 V AC
Connecting Capacity Auxiliary Circuit UL/CSA	Flexible 1/2x 16-14 AWG Stranded 1/2x 16-14 AWG
Tightening Torque UL/CSA	Auxiliary Circuit 7 in-Ib
Contact Rating UL/CSA	B300 R300
Environmental	
Ambient Air Temperature	Operation -25 +60 °C Storage -50 +80 °C
Resistance to Shock acc. to IEC 60068-2-27	11 ms Pulse 25g
Resistance to Vibrations	5g 3 150 Hz
Material Compliance	
Conflict Minerals Reporting Template (CMRT)	9AKK108467A5658
REACH Declaration	1SAA963005-4502

REACH Declaration	1SAA963005-4502
RoHS Information	1SAA963006-4502
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
Toxic Substances Control Act - TSCA	2CMT2023-006539
WEEE B2C / B2B	Business To Business
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

Certificates and Declarations	
A2L Certificate – IEC	1SAA963000-4601
CB Certificate	1SAA963003-2002
CQC Certificate	CQC2017010304032779
Declaration of Conformity - CCC	2020980304001251
Declaration of Conformity - CE	1SAD101100-3410
Declaration of Conformity - UKCA	1SAD201100-3410
LR Certificate	1SAA963001-0501 1SAA963001-0502 1SAA963000-0505 1SAA918001-0501
RINA Certificate	1SAA963002-0802
UL Certificate	UL_E137861

Container Information	
Package Level 1 Width	148 mm
Package Level 1 Depth / Length	36 mm
Package Level 1 Height	50 mm
Package Level 1 Gross Weight	0.195 kg
Package Level 1 EAN	4013614502651
Package Level 1 Units	box 10 piece
Package Level 2 Width	280 mm
Package Level 2 Depth / Length	395 mm
Package Level 2 Height	210 mm
Package Level 2 Gross Weight	10.125 kg
Package Level 2 EAN	4013614522758
Package Level 2 Units	500 piece

## Classifications

Object Classification	Q
Code	
ETIM 5	EC000041 - Auxiliary contact block
ETIM 6	EC000041 - Auxiliary contact block
ETIM 7	EC000041 - Auxiliary contact block
ETIM 8	EC000041 - Auxiliary contact block
eClass	V11.0 : 27371302
UNSPSC	39121522
IDEA Granular Category Code (IGCC)	4743 >> Auxiliary contact block
E-Number (Norway)	4364295

## Categories

Low Voltage Products and Systems  $\rightarrow$  Circuit Breakers  $\rightarrow$  Manual Motor Starters

Low Voltage Products and Systems  $\rightarrow$  Control Products  $\rightarrow$  Manual Motor Starters  $\rightarrow$  Manual Motor Starters

