

## Data sheet

US2:HNF362SPN

|                                                                                                        |                                             |
|--------------------------------------------------------------------------------------------------------|---------------------------------------------|
| Siemens Low Voltage Circuit Protection Heavy Duty Safety Switches. 60A<br>3P NF PN RECEPT SW STAINLESS |                                             |
| mechanical service life (operating cycles) typical                                                     | 10000                                       |
| fastening method                                                                                       | SURFACE                                     |
| number of poles                                                                                        | 3                                           |
| suitability for operation                                                                              | PROTECTION OF HEAVY DUTY PORTABLE EQUIPMENT |
| Electricity                                                                                            |                                             |
| ampacity                                                                                               | 60 A                                        |
| supply voltage frequency rated value 50/60 Hz                                                          | Yes                                         |
| Model                                                                                                  |                                             |
| product brand name                                                                                     | SIEMENS                                     |
| product type designation                                                                               | HEAVY DUTY SWITCH                           |
| special product feature                                                                                | ACCEPTS PYLE-NATIONAL QuelArc PLUGS         |
| type of electrical connection                                                                          | INTERLOCKED PLUG                            |
| Mechanical Design                                                                                      |                                             |
| design of the housing                                                                                  | TYPE 4X                                     |
| design of the actuating element                                                                        | SINGLE THROW                                |
| material                                                                                               | 304 STAINLESS STEEL                         |
| General product approval                                                                               |                                             |
| certificate of suitability                                                                             | UL98                                        |

last modified: 9/16/2021 

