


ø22 HW Series Maintenance Parts

Maintenance Parts

All dimensions in mm.

Shape	Material	Part No.	Quantity	Remarks
Contact Block HW-U  Weight: 11g (approx.)	NO contact	HW-U10	1	- Housing color: blue/Push rod color: green - MAU has gold contacts
		HW-U10-MAU		
	NC contact	HW-U01	1	- Housing color: reddish purple/Push rod color: red - MAU has gold contacts
		HW-U01-MAU		
	EM (early make) contact	HW-U10R	1	- Housing color: blue/Push rod color: black - MAU has gold contacts
		HW-U10R-MAU		
	LB (late break) contact	HW-U01R	1	- Housing color: reddish purple/Push rod color: white - MAU has gold contacts
		HW-U01R-MAU		
Dummy Block  Weight: 3.5g (approx.)	Polyamide	HW-DB	10	- For HW-U contact blocks - Used when the number of contact blocks and full voltage adapters is odd number.
Full Voltage Adapter for Illuminated (*1)  Weight: 12g (approx.)	Polyamide	HW-GA1N	2	- Applicable model: Illuminated pushbuttons Illuminated selector switches - Applicable load (LED lamp) LSRD-6, LSTD-6 (6V AC/DC) LSRD-1, LSTD-1 (12V AC/DC) LSRD-2, LSTD-2 (24V AC/DC)
Transformer Unit (*1)  Weight: 12g (approx.)	100/110V AC	HW-T16	1	- Applicable model: Illuminated pushbuttons Illuminated selector switches - Applicable load (LED lamp) LSRD-6, LSTD-6 (6V AC/DC) - For transformers with other primary voltages, please contact IDEC.
	200/220V AC	HW-T26	1	

*1) Maintenance parts are used for maintenance parts only. Do not use these parts for expansion or remodeling purpose.

Shape		Material/Dimensions	Part No.	Quantity	Color Code *
Lens 	①Round flush	Polyarylate ø23.5 H4.2	HW9Z-L11*-K	5	R (red), G (green), Y (yellow), A (amber), C (clear), S (blue) (*2)
	②Square flush	Polyarylate ø24.6 H4	HW9Z-L21*-K	5	
	③Round extended	Polyarylate ø23.3 H10	HW9Z-L12*-K	5	
	④ø29 mushroom	AS, marking type ø29 H12.7	ALW31LD--K	2	R (red), G (green),Y (yellow), A (amber), S (blue), C (clear) (*2)
	⑤ø40 mushroom	AS, marking type ø40 H12.7	ALW41LD--K	1	R (red), G (green), Y (yellow), A (amber), S (blue), C (clear) (*2)
	⑥Jumbo dome	Polycarbonate ø66 H50	HW1A-P5*	1	R (red), G (green), Y (yellow), A (amber), W (white), S (blue)
	⑦Dome for pilot light	AS ø23.5 H15.1	HW1A-P2*-K	5	R (red), G (green), Y (yellow), A (amber), W (white), S (blue) (*3)
Button 	①Round flush with round or square bezel	Polyacetal ø23.6 H3	HW1A-B1*	5	Use ① for pushbutton selectors. B (black), G (green), R (red), Y (yellow), S (blue), W (white)
	②Round extended with round or square bezel	Polyacetal ø23.6 H9.2	HW1A-B2*	5	
	③Square flush	Polyacetal □24.8 H3	HW2A-B1*	5	
	④Square extended	Polyacetal □24.5 H9.2	HW2A-B2*	5	
	⑤ø29 mushroom	Polyacetal ø29 H12.7(M18P1.0)	HW1A-B3*	2	
	⑥ø40 mushroom	Polyacetal ø40 H12.7(M18P1.0)	HW1A-B4*	2	

*2) Use C (clear) lens for PW (pure white) illumination.

*3) Use W (white) lens for PW (pure white) illumination.