

Manual Motor Starters MS 325

Accessories

Ordering details



Accessories

Type	Order code	Weight/ piece kg	Packing unit piece	Price
Phase buses for cross wiring MS 325, 63 A, 690 V				
PS3-2-0, for 2 dev., without aux. switch	1SAM 101 937 R 0012		10	
PS3-3-0, for 3 dev., without aux. switch	1SAM 101 937 R 0013		10	
PS3-4-0, for 4 dev., without aux. switch	1SAM 101 937 R 0014		10	
PS3-5-0, for 5 dev., without aux. switch	1SAM 101 937 R 0015		10	
PS3-2-1, for 2 dev., with 1 aux. switch	1SAM 101 937 R 0022		10	
PS3-3-1, for 3 dev., with 1 aux. switch	1SAM 101 937 R 0023		10	
PS3-4-1, for 4 dev., with 1 aux. switch	1SAM 101 937 R 0024		10	
PS3-5-1, for 5 dev., with 1 aux. switch	1SAM 101 937 R 0025		10	
PS3-2-2, for 2 dev., with 2 aux. switches	1SAM 101 937 R 0032		10	
PS3-4-2, for 4 devices, with 2 aux. swit.	1SAM 101 937 R 0034		10	
Power infeed blocks, 63 A, 690 V, stranded 25 mm², flexible 16 mm²				
S3- M1, flat	1SAM 101 938 R 0001		10	
S3- M2, high	1SAM 101 938 R 0002		10	
Cover for busbars (for not used poles)				
BS3-3	1SAM 101 938 R 0003		50	
Connecting element from MS 325 to 3-pole circuit-breaker S2				
SZ-SM3, for power infeed from top or bottom	GHV 036 0504 R 0005	0.047	1	
Insulating enclosure IP 65 with rotary handle, triple lockable in Off position, with N- und PE-terminal, for Manual Motor Starter				
IB 325-G, Twist knob black	1SAM 101 940 R1000	1		
IB 325-Y, Twist knob red/yellow	1SAM 101 940 R1001	1		
Insulating enclosure, light grey IP 55 with cover, including DIN rail for manual motor starter or line protection devices				
QES 4/3 N, for 4 modules, 72 mm	GHL 111 2304 R 0013			
QES 6/3 N, for 6 modules, 108 mm	GHL 111 2306 R 0013			
QES 10/3 N, for 10 modules, 180 mm	GHL 111 2310 R 0013			
Set of neutral and earth terminals				
SMO 4, for QES 4/3 N	GHL 430 1910 R 0004			
SMO 6, for QES 6/3 N	GHL 430 1910 R 0006			
SMO 10, for QES 10/3 N	GHL 430 1910 R 0010			
Plastic enclosure, light grey, IP40 in panel design, including DIN rail				
PCD 4 N, for 4 modules, 72 mm	GHS 270 1921 R 0004			
PCD 6 N, for 6 modules, 108 mm	GHS 270 1921 R 0006			
PCD 8 N, for 8 modules, 144 mm	GHS 270 1921 R 0008			
Switch cubicle mounting kit IP 65, with axial extension triple lockable in Off position, locked in On position				
OHB2AJM, Twist knob black	1SCA 022 384 R 6940		1	
OHY2AJM, Twist knob red/yellow ③	1SCA 022 384 R 7080		1	
OXS5X 85, axis 85 mm	1SCA 022 347 R 3570		1	
OXS5X105, axis 105 mm	1SCA 022 347 R 3650		1	
OXS5X130, axis 130 mm	1SCA 022 353 R 4540		1	
OXS5X180, axis 180 mm	1SCA 022 353 R 4620		1	
MSMN, driver ①	1SAM 101 923 R 0001		1	
MSOX, driver spindle 32 mm ②	1SAM 101 924 R 0001		1	
Direct adapter MS 325 ④				
BEA7/325, direct adapter MS325 to B6/B7	1SBN 080 906 R 1001	0.021	10	
BEA16/325, direct adapter MS325 to A9/A12/A16	1SBN 081 406 R 1001	0.031	10	
BEA26/325, direct adapter MS325 to A26	1SBN 082 406 R 1001	0.031	10	
Door mounting kit IP 65, Lockable in Off-position				
DMS 325-G, grey handle	1SAM 101 941 R 1000		1	
DMS 325-Y, red/yellow handle	1SAM 101 941 R 1001		1	

① For accommodating spindle and attachment to manual motor starter

② Is screwed directly onto the manual motor starter, ③ Only suitable for MS 325, ④ See also page 33