Product datasheet

Specification





integrated drive ILS with stepper motor - 24..36 V - CANopen DS301 - 3.5A

ILS1F571PB1A0

Main

Range of product	Lexium integrated drive	
Product or component type	Motion integrated drive	
Device short name	ILS	
Motor type	3-phase stepper motor	
Number of motor poles	6	
Network number of phases	Single phase	
[Us] rated supply voltage	36 V 24 V	
network type	DC	
Communication interface	CANopen DS301, integrated	
Length	101.9 mm	
Winding type	Medium speed of rotation and medium torque	
Electrical connection	Printed circuit board connector	
Holding brake	Without	
Gear box type	Without	
Nominal speed	1000 rpm at 36 V 500 rpm at 24 V	
Nominal torque	0.45 N.m	
Holding torque	0.51 N.m	

Complementary

Transmission rate	50, 100, 125, 250, 500, 800 and 1000 kbauds	
mounting support	Flange	
Motor flange size	57 mm	
Number of motor stacks	1	
Centring collar diameter	38.1 mm	
Centring collar depth	1.6 mm	
Number of mounting holes	4	
Mounting holes diameter	5.2 mm	
Circle diameter of the mounting holes	66.6 mm	
Feedback type	Index pulse	
Shaft end	Untapped	

Second shaft Without second shaft end	
Shaft diameter	6.35 mm
Shaft length	21 mm
Supply voltage limits	1840 V
Current consumption	3500 mA maximum
Associated fuse rating	10 A
Input/output type	4 signals (each be used as input or output)
Voltage state 0 guaranteed	-34.5 V
Voltage state 1 guaranteed	1530 V
Discrete input current	10 mA at 24 V on/STO_A for safety input 3 mA at 24 V on/STO_B for safety input 2 mA at 24 V for 24 V signal interface
Discrete output voltage	2325 V
Maximum switching current	100 mA per output 200 mA total
Protection type	Short circuit of the output voltage Safe torque off Overload of output voltage
Peak stall torque	0.45 N.m
Continuous stall torque	0.45 N.m
Speed feedback resolution	20000 points/turn
Accuracy error	+/- 6 arc min
Rotor inertia	0.1 kg.cm ²
Maximum mechanical speed	3000 rpm
Maximum radial force Fr	24 N
Maximum axial force Fa	100 N (tensile force) 8.4 N (force pressure)
Service life in hours	20000 h bearing
marking	CE
Type of cooling	Natural convection
Net weight	1.3 kg

Environment

Standards	IEC 61800-3, Ed 2 IEC 50347 IEC 61800-3 IEC 60072-1 EN 61800-3:2001, second environment EN 61800-3: 2001-02 IEC 50178
Product certifications	UL TÜV cUL
Ambient air temperature for operation	5065 °C (with power derating of 2 % per °C) 050 °C (without derating)
Permissible ambient air temperature around the device	105 °C power amplifier 110 °C motor
Ambient air temperature for storage	-2570 °C

Operating altitude	<= 1000 m without derating
Relative humidity	1585 % without condensation
Vibration resistance	20 m/s² (f= 10500 Hz) 10 cycles conforming to IEC 60068-2-6
Shock resistance	150 m/s² 1000 shocks conforming to IEC 60068-2-29
IP degree of protection	IP41 shaft bushing: conforming to IEC 60034-5 IP54 total except shaft bushing: conforming to IEC 60034-5

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	10.5 cm
Package 1 Width	17 cm
Package 1 Length	24.5 cm
Package 1 Weight	1.492 kg
Unit Type of Package 2	S04
Number of Units in Package 2	8
Package 2 Height	30 cm
Package 2 Width	40 cm
Package 2 Length	60 cm
Package 2 Weight	13.188 kg

Contractual warranty

Warranty 18 months



Green PremiumTM **label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

Well-being performance

	Mercury Free	
②	Rohs Exemption Information	Yes
	Pvc Free	

Certifications & Standards


Circularity Profile	End of Life Information
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Environmental Disclosure	Product Environmental Profile
China Rohs Regulation	China RoHS declaration
Eu Rohs Directive	Pro-active compliance (Product out of EU RoHS legal scope)
Reach Regulation	REACh Declaration

19 Aug 2024

Dimensions Drawings

Integrated Drive


Dimensions



- 1 Accessories: I/O signal insert with industrial connectors
- 2 Option: industrial connectors
- 3 Earth (ground) terminal
- 4 Accessories: cable entries $\emptyset = 3 \dots 9 \text{ mm}/0.12 \dots 0.35 \text{ in.}$
- L 101.9 mm/4.01 in.
- D 6.35 mm/0.25 in.

Connections and Schema

Connection Example with 4 I/O Signals




Product datasheet

ILS1F571PB1A0

Performance Curves

Torque Characteristics



- X Speed of rotation in rpm
- Y Torque in Nm
- 1.1 Max. torque at 24 V
- 1.2 Max. torque at 36 V