

PRODUCT-DETAILS

KA2-2232

KA2-2232 LED bulb



General Information	
Extended Product Type	KA2-2232
Product ID	1SFA616921R2232
EAN	7320500550021
Catalog Description	KA2-2232 LED bulb
Long Description	LED bulb - Green - Rated Voltage 230 V, AC/DC - Rated Current 4 mA - Service Life 25 000 h

Technical	
Suitable For	CL P9PD
Suitable for Product Class	Pilot Devices
Rated Operational Voltage	230 V AC/DC
Rated Current (I _n)	4 mA
Product Range	Compact and Modular range
Accessory Type	LED and filament bulbs
Lamp Type	LED Ba9s
Product Type	KA
Illumination	Illuminated
Color	Green

Environmental	
Ambient Air Temperature	Operation -25 +70 °C Storage -40 +85 °C
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
Environmental Information	1SFC151005D0201

Dimensions	
Product Net Width	0.01 m
Product Net Height	0.01 m
Product Net Depth / Length	0.025 m
Product Net Weight	0.005 kg

Container Information	
box 20 piece	
0.06 m	
0.01 m	
0.025 m	
0.1 kg	
7320500359617	

20 piece
8539500000
2312849

Certificates and Declarations (Document Number)	
Declaration of Conformity - CE	2CMT2015-005456
Environmental Information	1SFC151005D0201
Instructions and Manuals	1SFC151011M0201
RoHS Information	2CMT2015-005456

Popular Downloads	
Data Sheet, Technical Information	1SFC151007C02_
Instructions and Manuals	1SFC151011M0201

Classifications	
ETIM 7	EC000399 - Indication- and signalling lamp
ETIM 8	EC000399 - Indication- and signalling lamp
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
WEEE B2C / B2B	Business To Business
CN8	8539 50 00

KA2-2232 3

UNSPSC	39121500
eClass	V11.0 : 27110631
Object Classification	E
Code	

Categories

 $\textbf{Low Voltage Products and Systems} \rightarrow \textbf{Control Products} \rightarrow \textbf{Pilot Devices} \rightarrow \textbf{Accessories}$

