





Safety switch, light duty, fusible, 30A, 3 wire, 2 poles, 1 neutral, 240VAC, Type 1

L221N

Product availability: Stock - Normally stocked in distribution facility

Price\*: 98.00 USD

### Main

Product	Single Throw Safety Switch	
Duty Rating	Light duty	
Device Application	Furnace Garages	
Disconnect Type	Fusible disconnect	
Factory Installed Neutral	Neutral (factory installed)	
Phase	3 phase	
Number of Poles	2	
Current Rating	30 A	
Voltage Rating	240 V AC	
NEMA degree of protection	NEMA 1	
Motor power hp	0.5 hp at 120 V AC 50-60 Hz for 1 phase motors 2 hp at 120 V AC 50-60 Hz for 1 phase motors 1.5 hp at 240 V AC 50-60 Hz for 1 phase motors 3 hp at 240 V AC 50-60 Hz for 1 phase motors	

## Complementary

Short-circuit current	10 kA	
Fuse Type	H or J	
Mounting Type	Surface	
Wire Size	AWG 14AWG 8 copper AWG 12AWG 8 aluminium	
Tightening torque	30 lbf.in (3.39 N.m) 0.000.01 in² (2.0828.367 mm²) (AWG 14AWG 8) 30 lbf.in (3.39 N.m) 0.010.01 in² (3.3078.367 mm²) (AWG 12AWG 8)	
Depth	4 in (101.6 mm)	
Width	6.13 in (155.70 mm)	
Height	7.63 in (193.80 mm)	

#### **Environment**

Product Certifications UL listed file E2875

### Ordering and shipping details

Category US1DE1A00057

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Discount Schedule	DE1A
GTIN	785901499022
Returnability	Yes
Country of origin	MX

# **Packing Units**

Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Height	4.50 in (11.43 cm)	
Package 1 Width	6.800 in (17.272 cm)	
Package 1 Length	8.900 in (22.606 cm)	
Package 1 Weight	3.360 lb(US) (1.524 kg)	
Unit Type of Package 2	PAL	
Number of Units in Package 2	200	
Package 2 Height	40.0000000000 in (101.6 cm)	
Package 2 Width	40.000000000 in (101.6 cm)	
Package 2 Length	48.000000000 in (121.92 cm)	
Package 2 Weight	698.00 lb(US) (316.607 kg)	

# **Contractual warranty**

Warranty 18 months



**Green Premium**<sup>TM</sup> **label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

## Well-being performance

<b>②</b>	Reach Free Of Svhc	
<b>Ø</b>	Toxic Heavy Metal Free	
<b>Ø</b>	Mercury Free	
<b>Ø</b>	Rohs Exemption Information	Yes

#### **Certifications & Standards**

Reach Regulation	REACh Declaration
Eu Rohs Directive	Compliant
	EU RoHS Declaration
China Rohs Regulation	China RoHS declaration
	Pro-active China RoHS declaration (out of China RoHS legal scope)
Environmental Disclosure	Product Environmental Profile
Circularity Profile	No need of specific recycling operations
California Proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov