## **Product data sheet**

Specifications





# Suppressor module, TeSys Deca, varistor, 24 to 48VAC

LA4DE2E

Product availability: Stock - Normally stocked in distribution facility

Price\*: 31.44 USD

## Main

| Range                     | TeSys             |
|---------------------------|-------------------|
| Device short name         | LA4D              |
| Product or Component Type | Suppressor module |
| Product compatibility     | 4P LC1D80D115     |
| • •                       | 3P LC1D80D115     |

## Complementary

| mounting location            | Тор                      |
|------------------------------|--------------------------|
| Mounting Mode                | By screws                |
| Suppressor technology        | Varistor (peak limiting) |
| [Uc] control circuit voltage | 2448 V AC                |
| Maximum peak voltage         | 2 Uc                     |
| Net Weight                   | 0.040 lb(US) (0.018 kg)  |

## **Environment**

| Standards                                | IEC 60947-5-1<br>EN 60947-5-1<br>CSA C22.2 No 60947-5-1<br>UL 60947-5-1<br>GB/T 14048.5 |
|--|---|
| Product Certifications                   | UL<br>CSA   |
| IP degree of protection                  | IP2XIEC 60529   |
| Ambient Air Temperature for<br>Operation | -13.0000000000131.0000000000 °F (-2555 °C)  |
| Ambient Air Temperature for Storage      | -40.0000000000176.0000000000 °F (-4080 °C)  |

## Ordering and shipping details

| Category          | US10I1222341  |  |
|-------------------|---------------|--|
| Discount Schedule | 0112          |  |
| GTIN              | 3389110233100 |  |
| Returnability     | No            |  |
| Country of origin | US            |  |

## **Packing Units**

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

| Unit Type of Package 1       | PCE                     |
|------------------------------|-------------------------|
| Number of Units in Package 1 | 1                       |
| Package 1 Height             | 2.0 in (5 cm)           |
| Package 1 Width              | 1.6 in (4.1 cm)         |
| Package 1 Length             | 1.06 in (2.7 cm)        |
| Package 1 Weight             | 0.5 oz (14 g)           |
| Unit Type of Package 2       | S01                     |
| Number of Units in Package 2 | 78                      |
| Package 2 Height             | 5.9 in (15 cm)          |
| Package 2 Width              | 5.9 in (15 cm)          |
| Package 2 Length             | 15.7 in (40 cm)         |
| Package 2 Weight             | 2.853 lb(US) (1.294 kg) |

## **Contractual warranty**

Warranty 18 months



**Green Premium**<sup>TM</sup> **label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

## Well-being performance

| <b>⊘</b> | Reach Free Of Svhc         |     |
|----------|----------------------------|-----|
| <b>⊘</b> | Toxic Heavy Metal Free     |     |
| <b>⊘</b> | Mercury Free               |     |
| <b>⊘</b> | Rohs Exemption Information | Yes |

#### **Certifications & Standards**

| Reach Regulation         | REACh Declaration  |
|--------------------------|--|
| Eu Rohs Directive        | Compliant EU RoHS Declaration  |
| China Rohs Regulation    | China RoHS declaration  Pro-active China RoHS declaration (out of China RoHS legal scope)                                    |
| Environmental Disclosure | Product Environmental Profile  |
| Weee                     | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins. |
| Circularity Profile      | No need of specific recycling operations   |