# Product data sheet

Specifications





# Suppressor module, TeSys Deca, varistor, 50 to 127VAC

LA4DE2G

Product availability: Stock - Normally stocked in distribution facility

#### Price\*: 47.16 USD

#### Main

| Range                     | TeSys                          |  |
|---------------------------|--------------------------------|--|
| Device short name         | LA4D                           |  |
| Product or Component Type | Suppressor module              |  |
| Product compatibility     | 4P LC1D80D115<br>3P LC1D80D115 |  |

#### Complementary

| mounting location            | Тор                      |
|------------------------------|--------------------------|
| Mounting Mode                | By screws                |
| Suppressor technology        | Varistor (peak limiting) |
| [Uc] control circuit voltage | 50127 V AC               |
| Maximum peak voltage         | 2 Uc                     |
| Net Weight                   | 0.040 lb(US) (0.018 kg)  |

#### Environment

| IEC 60947-5-1<br>EN 60947-5-1             |  |
|---|--|
| CSA C22.2 No 60947-5-1                    |  |
| UL 60947-5-1                              |  |
| GB/T 14048.5                              |  |
| UL  |  |
| CSA                                       |  |
| IP2XIEC 60529                             |  |
| -13.000000000131.000000000 °F (-2555 °C)  |  |
| -40.000000000176.0000000000 °F (-4080 °C) |  |
|   | EN 60947-5-1<br>CSA C22.2 No 60947-5-1<br>UL 60947-5-1<br>GB/T 14048.5<br>UL<br>CSA<br>IP2XIEC 60529<br>-13.000000000131.000000000 °F (-2555 °C) |

# Ordering and shipping details

| Category          | US10I1222341  |
|-------------------|---------------|
| Discount Schedule | 0112          |
| GTIN              | 3389110233117 |
| Returnability     | No            |
| Country of origin | FR            |

# **Packing Units**

Price is "List Price" and may be subject to a trade discount - check with your local distributor or retailer for actual price.

| Unit Type of Package 1       | PCE                     |
|------------------------------|-------------------------|
| Number of Units in Package 1 | 1                       |
| Package 1 Height             | 1.969 in (5.000 cm)     |
| Package 1 Width              | 1.614 in (4.100 cm)     |
| Package 1 Length             | 1.063 in (2.700 cm)     |
| Package 1 Weight             | 0.459 oz (13.000 g)     |
| Unit Type of Package 2       | S01                     |
| Number of Units in Package 2 | 78                      |
| Package 2 Height             | 5.906 in (15.000 cm)    |
| Package 2 Width              | 5.906 in (15.000 cm)    |
| Package 2 Length             | 15.748 in (40.000 cm)   |
| Package 2 Weight             | 2.718 lb(US) (1.233 kg) |

# **Contractual warranty**

Warranty

18 months

# Sustainability Screen Premium

**Green Premium<sup>TM</sup> label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >



Transparency RoHS/REACh

### Well-being performance

Reach Free Of Svhc
Toxic Heavy Metal Free
Mercury Free
Rohs Exemption Information Yes

#### **Certifications & Standards**

| Reach Regulation         | REACh Declaration  |
|--------------------------|--|
| Eu Rohs Directive        | Compliant<br>EU RoHS Declaration   |
| China Rohs Regulation    | China RoHS declaration<br>Pro-active China RoHS declaration (out of China RoHS legal scope)                                  |
| Environmental Disclosure | Product Environmental Profile  |
| Weee                     | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins. |
| Circularity Profile      | No need of specific recycling operations   |