Product data sheet

Specification





electronic timer module - type on delay 25...500 s - 24...250 V DC/AC

LA4DT4U

Product availability: Stock - Normally stocked in distribution facility

Price*: 98.40 USD

Main

Range	TeSys	
Product or Component Type	Serial timer modules	
Device short name	LA4DT	
poles description	3P	
Product Compatibility	LC1D09D38	
	LC1D80D150	
	LC1D40AD80A	

Complementary

mounting location	Тор	
[Uc] control circuit voltage	24250 V AC 50/60 Hz 24250 V DC	
Control circuit voltage limits	By mechanical contact: 0.81.1 Uc	
[Ui] rated insulation voltage	250 V IEC 60947-1	
Connections - terminals	Control circuit connector 1 0.0020.004 in² (12.5 mm²)flexible with cable end Control circuit connector 1 0.0020.004 in² (12.5 mm²)solid with cable end Control circuit connector 1 0.0020.004 in² (12.5 mm²)solid without cable end Control circuit connector 1 0.0020.004 in² (12.5 mm²)solid without cable end Control circuit connector 2 0.0020.004 in² (12.5 mm²)solid without cable end Control circuit connector 2 0.0020.004 in² (12.5 mm²)solid with cable end Control circuit connector 2 0.0020.004 in² (12.5 mm²)solid without cable end Control circuit connector 2 0.0020.004 in² (12.5 mm²)solid without cable end	
Tightening torque	15.05 lbf.in (1.7 N.m)	
Electrical durability	30 Mcycles	
Timer type	On delay	
time delay range	25500 s	
Reset time	150 ms during time delay 50 ms after time delay	
local signalling	Illuminates during time delay by LED	
[Ures] residual voltage	3.3 V	
Net Weight	0.09 lb(US) (0.04 kg)	

Environment

Standards	IEC 60255-5
Product Certifications	UL CSA

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

IP degree of protection	IP2X conforming to IEC 60529	
Ambient Air Temperature for Operation	-13.0000000000131.0000000000 °F (-2555 °C)	
Permissible ambient air temperature around the device	-13.0000000000158.0000000000 °F (-2570 °C)	
Ambient Air Temperature for Storage	-40.0000000000176.0000000000 °F (-4080 °C)	
Protection Type	Built-in by varistor	
Heat dissipation	2 W	
Immunity to microbreaks	10 ms during time delay 2 ms after time delay	

Ordering and shipping details

Category	US10I1222341	
Discount Schedule	0112	
GTIN	3389110192780	
Returnability	Yes	
Country of origin	FR	

Packing Units

Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Height	1.600 in (4.064 cm)	
Package 1 Width	1.900 in (4.826 cm)	
Package 1 Length	2.0000000000 in (5.08 cm)	
Package 1 Weight	1.60 oz (45.36 g)	
Unit Type of Package 2	S02	
Number of Units in Package 2	70	
Package 2 Height	5.9 in (15 cm)	
Package 2 Width	11.8 in (30 cm)	
Package 2 Length	15.7 in (40 cm)	
Package 2 Weight	8.428 lb(US) (3.823 kg)	

Contractual warranty

Warranty 18 months



Green PremiumTM **label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

Well-being performance

⊘	Toxic Heavy Metal Free	
⊘	Mercury Free	
⊘	Rohs Exemption Information	Yes

Certifications & Standards

Reach Regulation	REACh Declaration
Eu Rohs Directive	Compliant with Exemptions
China Rohs Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information.
Environmental Disclosure	Product Environmental Profile
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.
Circularity Profile	No need of specific recycling operations