



LADR43

Product availability: Non-Stock - Not normally stocked in distribution facility



#### Main

wain		
Range	TeSys	
	TeSys Deca	
Product name	TeSys Deca	
Product or Component Type	Time delay auxiliary contact block	
Range compatibility	TeSys D CAD TeSys D LC1D TeSys Deca CAD TeSys Deca LC1D	
mounting location	Front	
Pole contact composition	1 NO + 1 NC	
Contacts operation	Time delay	
Timer type	Off delay	
time delay range	10180 s	
[Ue] rated operational voltage	690 V AC 25400 Hz	
[le] rated operational current	6 A at 120 V AC-15 1.04 A at 690 V AC-15 0.55 A at 125 V DC-13 0.1 A at 600 V DC-13	
[Ui] rated insulation voltage	690 V IEC 60947-5-1 600 V UL 60947-5-1 600 V CSA C22.2 No 60947-5-1	
[Ith] conventional free air thermal current	10 A (at 140 °F (60 °C))	
Standards	EN/IEC 60947-5-1 UL 60947-5-1 CSA C22.2 No 60947-5-1 GB/T 14048.5 EN 50012 IEC 60335-1:Clause 30.2 IEC 60335-2-40:Annex JJ UL 60335-2-40:Annex JJ	
Product Certifications	IECEE CB Scheme UL CSA CCC EAC	

### Complementary

Irms rated making capacity	140 A AC	
	250 A DC	

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Permissible short-time rating	100 A 140 °F (60 °C) 1 s
	120 A 140 °F (60 °C) 500 ms
	140 A 140 °F (60 °C) 100 ms
Protection type	GG fuse 10 A
Mechanical durability	5 Mcycles
Minimum switching current	5 mA
Minimum switching voltage	17 V
Non-overlap time	1.5 ms on de-energisation no overlap between NC and NO contact
	1.5 ms on energisation no overlap between NC and NO contact
Insulation resistance	> 10 MOhm
Connections - terminals	spring terminals 2 0.004 in <sup>2</sup> (2.5 mm <sup>2</sup> )flexible without cable end
	spring terminals 2 0.004 in <sup>2</sup> (2.5 mm <sup>2</sup> )rigid without cable end
Height	1.9 in (48 mm)
Width	1.7 in (44 mm)
Depth	2.4 in (61 mm)
color	Dark grey

### **Environment**

Environmental characteristic	Normal environment
IP degree of protection	IP20 conforming to IEC 60529
Protective treatment	TH IEC 60068
Ambient Air Temperature for Storage	-76176 °F (-6080 °C)
Ambient Air Temperature for Operation	-40158 °F (-4070 °C)
Operating altitude	9842.52 ft (3000 m)

# Ordering and shipping details

Category	US10I1222341	
Discount Schedule	0112	
GTIN	3389110821895	
Returnability	No	
Country of origin	FR	

# **Packing Units**

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	2.05 in (5.2 cm)
Package 1 Width	2.6 in (6.5 cm)
Package 1 Length	1.9 in (4.7 cm)
Package 1 Weight	2.8 oz (80.0 g)
Unit Type of Package 2	S01
Number of Units in Package 2	32
Package 2 Height	5.9 in (15.0 cm)
Package 2 Width	5.9 in (15.0 cm)

Package 2 Length	15.7 in (40.0 cm)
Package 2 Weight	6.140 lb(US) (2.785 kg)

## **Contractual warranty**

Warranty 18 months

## Sustainability Screen Premium

**Green Premium**<sup>TM</sup> **label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

### Well-being performance



#### **Certifications & Standards**

Reach Regulation	REACh Declaration
Eu Rohs Directive	Compliant with Exemptions
China Rohs Regulation	China RoHS declaration  Product out of China RoHS scope. Substance declaration for your information.
Environmental Disclosure	Product Environmental Profile
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.
Circularity Profile	No need of specific recycling operations
California Proposition 65	WARNING: Cancer - www.P65Warnings.ca.gov